**Engineering Evaluation Report** 

L. Roberto Lomas P.E.

208 7<sup>th</sup> Ave Indialantic, FL 32903 434-688-0609 rllomas@lrlomaspe.com

# Report No.: 515329

Manufacturer:	C.R. Laurence Co., Inc.
	2503 E. Vernon Ave,
	Los Angeles, CA 90058

Product Line: Entice HP+ Single Side Hinged Door, Non-Impact

## Compliance:

The product listed herein complies with requirements of the Florida Building Code.

### Supporting Technical Documentation:

- 1. Approval document: drawing number 08-04018, prepared, signed and sealed by Luis Roberto Lomas P.E.
- Test report No.: Q5257.01-303-47 signed and sealed by Tyler Westerling P.E. Intertek, Lake Forest, CA AAMA/WDMA/CSA 101/I.S.2/A440 Design pressure: ±30.08psf
- 3. Anchor calculations with comparative analysis, report number 515329-1, prepared, signed and sealed by Luis Roberto Lomas P.E.

### Limitations and Conditions of use:


- Design pressure: Refer to installation drawing
- Unit size: Refer to installation drawing
- Units must be glazed per ASTM E1300, with safety glazing.
- This product is not rated to be used in the HVHZ.
- This product is not impact resistant and requires impact protection in wind borne debris regions.
- Frame material to be Aluminum 6063-T6 with Steel Cladding.
- This system was not tested for water penetration infiltration and must be installed in locations where water penetration resistance is not required.

### Installation:

Units must be installed in accordance with manufacturer's installation instructions and approval document 08-04018.

### Certification of Independence:

Please note that I do not have nor will acquire a financial interest in any company manufacturing or distributing the product(s) for which this report is being issued. Also, I do not have nor will acquire a financial interest in any other entity involved in the approval process of the listed product(s).



Luis R. Lomas, P.E. FL No.: 62514 04/16/2024