


COMPANY NAME _____
CONTACT _____ ACCOUNT NO. _____
JOB NAME _____

PHONE _____
FAX _____
EMAIL _____

☐ QUOTE ☐ ORDER P.O. # _____ DATE _____

SERIES	THICKNESS	STANDARD PROFILE DIMENSIONS		
		STILE	TOP RAIL	BOTTOM RAIL
IG500	2-3/16"	4-5/8"	4-11/16"	7-5/16"
IG600	2-3/16"	4-5/8"	4-11/16"	7-5/16"
IT600	2-3/16"	4-5/8"	4-11/16"	7-5/16"
Special Top Rail for Overhead Concealed Closer Bottom Rail Option			5-11/16"	10"

DOOR SWING CHART



Use the Door Swing Chart to determine how the door(s) should be handed.

OPENING TYPE

- ☐ Door and Frame (Supply) ☐ Frame Only (Supply)
☐ Door Only (Supply) ☐ Custom _____

DOOR STILE

IG500
IG600
IT600

GLASS STOPS

- ☐ With 9/16" Glass Stops
- ☐ With 1-5/16" Glass Stops
- ☐ With 1-5/16" Glass Stops

DOOR FINISH

- ☐ 11 - Clear Anodized
☐ 22 - Dark Bronze Anodized
☐ 33 - Black Anodized
☐ 52 - Bone White 70% KYNAR[®] (2-Coat)
☐ 71 - Standard 70% KYNAR[®] (2-Coat)
Standard Color per Chart - Specify _____
☐ 71 - Custom 70% KYNAR[®] (2-Coat) - Specify _____
☐ 71 - Custom 70%KYNAR[®](3-Coat) - Specify _____

TOP RAIL

- ☐ 4-11/16" (Standard)
☐ 5-11/16" for OHCC

BOTTOM RAIL

- ☐ 7-5/16" (Standard)
☐ 10" Bottom

DOOR MUNTIN

- ☐ 7-5/16" Horizontal (only) (NON FPA)
From Bottom of Door to Center Line of Muntin
(Specify) _____

DOOR HINGING

- ☐ Continuous Geared Hinge (Florida Approval)
☐ 1-1/2" PR Butt Hinges
☐ By USALUM ☐ By Others
NOTE: Prep Only Requires Manufacturer's Name,
Model, and Template
Manufacturer: _____
Model: _____

CLEARANCES/THRESHOLDS

- These Thresholds Follow FPA Guidelines
Clearance from Bottom of Door to Finish Floor
- ☐ TH811 3/8" (Air Threshold)
- ☐ TH800 1-3/4" (Air Water Threshold)
(Includes IG570 Sub sill)
(Accessible Threshold Ramp Not Included)

DOOR CLOSER

- ☐ O.H. Concealed (Offset-Prep Only)
☐ Jackson 20-330
☐ LCN 2030
☐ 90° ☐ 105°
☐ Hold Open ☐ Yes ☐ No
☐ Surface Mount
☐ Drop Plate
☐ Door Stop/Holder Degree _____
☐ No Closer Required

LOCKING

- ☐ A.R. MS Hookbolt With Cylinder/T-Turn - **STD**
• Cylinder (Ext.) • Thumbturn (Int.)
☐ Flushbolts - DH008 - **STD**
☐ A.R. MS188 Two Points Flushbolts (Optional)

HARDWARE FINISH

DOOR FINISH

- Clear 11, 12, 44, 52, 71
• Bronze 22, 33
☐ Specify _____

DOOR OPENING SIZE

- ☐ 36" x 84"
☐ Custom Single _____
(FPA Maximum Size 36" x 96")
☐ 72" x 84"
☐ Custom Pair _____
(FPA Maximum Size 72" x 96")

DOOR SWING

QUANTITY

- ☐ LHR Hinge Left Swing Out _____ ea.
☐ RHR Hinge Right Swing Out _____ ea.
☐ PAIR Swing Out _____ ea.

FOR OFFICE USE ONLY

TAKEN BY: _____
PRICED BY: _____
EDITED BY: _____

PANIC DEVICES

- Concealed Vertical Rod Panics
- ☐ Jackson 1285
 - ☐ Jackson 2086
 - ☐ With Cylinder on Active Leaf
 - ☐ Exit Only

FRAME SERIES

Series IG500
Series IG600
Series IT600

UP/OVER FRAME

- ☐ Up/Over
- ☐ Up/Over
- ☐ Up/Over

TRANSOM FRAME

- ☐ Transom (120" Max Height)
- ☐ Transom (120" Max Height)
- ☐ Transom (120" Max Height)

PUSH/PULL HARDWARE

- ☐ Standard Push/Pull
- ☐ Offset Pulls
- ☐ None

ADDITIONAL NOTES OR SKETCHES

APPROVED BY _____ **DATE** _____

NOTE: PLEASE DOWNLOAD FORM TO SUBMIT. DO NOT FILL FORM ONLINE.

Email completed form to us_alum@usalum.com.
Fax checklist to U.S. Aluminum Technical Sales at (877) 883-7547
To review call (800) 627-6440. This form is available online at usalum.com.

FOR OFFICE USE ONLY

TAKEN BY: _____

PRICED BY: _____

EDITED BY: _____