

## **Quote/Order Request Form**

Name	
Email	
Phone	Number

When you are ready to order, utilize this form to assist you in covering the details required to complete a Klarity Interior Partition Post System installation. Going through this exercise should prevent you from overlooking any details related to your installation.

NOTE: Shop drawings required (included).

Date

Company	
Account Number	
Job Name	

**IMPORTANT:** Depending on the complexity of your project, one or more of the following may be required to accurately order: sketches or drawings of your particular application with dimensions; printed architectural drawings or CAD files; photos of the job site conditions (digital images are preferable).

**NOTE:** A final sign off is required prior to any custom fabrication.

**POST HEIGHT GLASS THICKNESS** DOORS 60" (1524 mm) □ 1/2" Monolithic Tempered □ Sliding Door 72" (1829 mm) 9/16" Laminated Tempered Swing Door 84" (2134 mm) P-Type (Glass not supplied by CRL) Custom BP-Type \*Standard 🗌 А-Туре P-TYPE **BP-TYPE** A-TYPF FINISH No Lock With Lock Available finish options: Bottom Rail Lock Brushed Stainless Steel (P-Type / BP-Type) Polished Stainless Steel AMR205 Patch Lock (A-Type) Powder Coat (Specify) Locking Ladder Pull (Lock Down) \*If locking hardware is required, only a bottom rail lock or bottom locking ladder pull can be used. LAYOUT GRID TO SKETCH DESIGN NOTES

RESET BUTTON

Please submit to: entrance.partitions@crlaurence.com