

CLASSIQUE

Wall Mount Hinge – Standard Back Plate

CAT. NO. CLA037

***NOTE:** Do not exceed either maximum weight or width when choosing proper quantity of hinges.

Specifications:

Glass Sizes: 5/16" (8mm) to 3/8" (10mm) thick tempered safety glass
 Construction: Solid brass
 Closing Type: Self-centering when within 15° of closed position
 Cutout Required
 Includes: Gaskets, screws and template

Maximum Door Capacities for Two Hinges or Three Hinges

Maximum Door Weight:	80 lbs. (36 kg)	120 lbs. (55 kg)
Maximum Door Width:	31" (787mm)	34" (864mm)

Use of Gaskets:

For 5/16" (8mm) Glass: Use one thick gasket on each side
 For 3/8" (10mm) Glass: Use one thin gasket on one side and a thick gasket on the other side



Recommendations:

For public safety, we recommend the use of only tempered safety glass. Do not use power tools when installing these hinges.

Maintenance Guidelines:

- Never use an abrasive cleaner on the hardware. Many of the components are coated with a clear lacquer that will be irreparably damaged if subjected to harsh, abrasive chemicals. Advise your customer that drying the hardware with a clean, soft towel on a daily basis is the best way to maintain the hardware. If mineral deposits build-up, mix a couple of drops of a mild liquid soap (such as Ivory or a similar product) into a cup of warm water. Using a soft, non-abrasive cloth, clean the hardware. Rinse thoroughly with clean, warm water and dry.

IMPORTANT: Project measurements from the edge of the glass.



CLASSIQUE

Wall Mount Hinge – Standard Back Plate

CAT. NO. CLA037