

S A F E T Y D A T A S H E E T

1. Product and Company Identification

Product Code: 3379520
Product Name: AMAZ WATER STAIN REMOVER
Company Name: GEIL ENTERPRISES, INC. **Phone Number:**
600 West Locust Avenue (559)495-3000
Suite 102
Fresno, CA 93650-1094
Emergency Contact: CERTS (Health & Environmental only) (800)552-3787
Information: (559)495-3000

2. Hazards Identification

Target Organ Systemic Toxicity (repeated exposure), Category 2

Aspiration Toxicity, Category 1

Acute Toxicity: Oral, Category 4



GHS Signal Word: Danger

GHS Hazard Phrases: H373 - May cause damage to organs through prolonged or repeated exposure.
H304 - May be fatal if swallowed and enters airways.
H302 - Harmful if swallowed.
H315 - Causes skin irritation.
H318 - Causes serious eye damage.

GHS Precaution Phrases: P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P362+364 - Take off contaminated clothing and wash it before reuse.

GHS Response Phrases: P314 - Get medical attention/advice if you feel unwell.
P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331 - Do NOT induce vomiting.
P301+312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P330 - Rinse mouth.
P302+352 - IF ON SKIN: Wash with plenty of soap and water.
P321 - Specific treatment see ... on this label.
P332+313 - If skin irritation occurs, get medical advice/attention.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER/doctor/....

GHS Storage and Disposal Phrases: P501 - Dispose of contents/container to
P405 - Store locked up.

Hazard Rating System:

HEALTH	1
FLAMMABILITY	0
PHYSICAL	0
PPE	B

HMIS:
Potential Health Effects (Acute and Chronic):

Breathing dusts may result in silicosis.

Prolonged or repeated skin contact may cause defatting and dermatitis.

Chronic:

Inhalation:

Inhalation of vapors or dust is extremely irritating.

Skin Contact:

May cause skin irritation. May cause irritation with burning pain, itching and redness. Prolonged and/or repeated contact may cause irritation and/or dermatitis.

Eye Contact:

Causes eye irritation.

Ingestion:

May be harmful if swallowed.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
14808-60-7	Quartz {Silica-crystalline; Cistobalite; Tridymite}	<=70.0 %
64742-47-8	Hydrotreated light distillate (petroleum)	<=4.0 %
2717-15-9	9-Octadecenoic acid (z)-, compd. with 2,2',2''-nitrilotris[e	<=4.0 %

4. First Aid Measures

Emergency and First Aid Procedures:
In Case of Inhalation:

If breathed in, move person into fresh air. Consult a physician. If inhaled, remove to fresh air. If breathing is difficult, give oxygen.

In Case of Skin Contact:

Wash off with soap and plenty of water. Get medical aid if irritation develops and persists. Wash clothing before reuse.

In Case of Eye Contact:

Flush eyes with water as a precaution.

In Case of Ingestion:

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Signs and Symptoms Of Exposure:

Breathing dusts from the use of this product may be harmful.

Prolonged inhalation of crystalline silica may result in silicosis, a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lungs, a dry cough, shortness of breath, emphysema, decreased chest expansion, and increased susceptibility to tuberculosis. In advanced stages, loss of appetite, pleuritic pain, and total incapacity to work. Advanced silicosis may result in death due to cardiac failure or destruction of lung tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of carcinogenicity by the NTP.

The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time.

Note to Physician:

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. None known.

5. Fire Fighting Measures

Flash Pt:

Explosive Limits: LEL: UEL:

Autoignition Pt:

Suitable Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray, dry chemical, carbon dioxide, or appropriate foam.

Fire Fighting Instructions: Wear self contained breathing apparatus for fire fighting if necessary.

Further information.

The product itself does not burn. As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool.

Flammable Properties and Hazards:

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled: Personal precautions.
Use personal protective equipment. Avoid dust formation. Avoid breathing vapors, mist or gas. Avoid breathing dust.
Environmental precautions.
Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal. Use proper personal protective equipment as indicated in Section 8.

7. Handling and Storage

Precautions To Be Taken in Handling: Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Provide appropriate exhaust ventilation at places where dust is formed. Wash thoroughly after handling. Keep container tightly closed. Avoid ingestion and inhalation.

Precautions To Be Taken in Storing: Keep in a dry place. Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances. Keep containers tightly closed.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
14808-60-7	Quartz {Silica-crystalline; Cistobalite; Tridymite}	PEL: 8825 ppm/(%SiO ₂ +5)	TLV: 0.05 mg/m ³ (R)	
64742-47-8	Hydrotreated light distillate (petroleum)		TLV: 200 mg/m ³	
2717-15-9	9-Octadecenoic acid (z)-, compd. with 2,2',2"-nitrilotris[e			

Respiratory Equipment (Specify Type):	Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Eye Protection:	Safety glasses with side-shields conforming to EN166. Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166. Wear chemical splash goggles.
Protective Gloves:	Rubber gloves.
Other Protective Clothing:	
Engineering Controls (Ventilation etc.):	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate ventilation to keep airborne concentrations low.
Work/Hygienic/Maintenance Practices:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. Physical and Chemical Properties

Physical States:	<input type="checkbox"/> Gas <input type="checkbox"/> Liquid <input checked="" type="checkbox"/> Solid	
Appearance and Odor:	Paste. solvent odor.	
Melting Point:	NP	
Boiling Point:		
Autoignition Pt:		
Flash Pt:		
Explosive Limits:	LEL:	UEL:
Specific Gravity (Water = 1):	2.98	at 70.0 F
Vapor Pressure (vs. Air or mm Hg):		
Vapor Density (vs. Air = 1):		
Evaporation Rate:		
Solubility in Water:	< 30	at 70.0 F
pH:	7 - 9	
Percent Volatile:	<= 30.0 % by weight.	
VOC / Volume:	104.0000 G/L	

10. Stability and Reactivity

Stability:	Unstable <input type="checkbox"/> Stable <input checked="" type="checkbox"/>
Conditions To Avoid - Instability:	No data available. ignition sources, Extreme temperatures.
Incompatibility - Materials To Avoid:	Hydrogen fluoride, Strong acids.
Hazardous Decomposition Byproducts:	Or formed under fire conditions. Nitrogen oxides, Carbon monoxide, oxides of sulfur.
Possibility of Hazardous Reactions:	Will occur <input type="checkbox"/> Will not occur <input checked="" type="checkbox"/>
Conditions To Avoid - Hazardous Reactions:	

11. Toxicological Information

Toxicological Information: Acute toxicity. No data available.
 Respiratory or skin sensitization: Germ cell mutagenicity. Reproductive toxicity - no data available.
 Specific target organ toxicity -single exposure (Globally Harmonized System) Specific target organ toxicity -repeated exposure (Globally Harmonized System)
 Inhalation: May cause damage to organs through prolonged or repeated exposure. Aspiration hazard. Epidemiology: No information found.
 Teratogenicity: No information available. Reproductive Effects: Neurotoxicity: These effects are likely associated with zinc deficiency due to chelation. Exposures having no effects on the mother should have no effects on the fetus.

Irritation or Corrosion: No data available.

Carcinogenicity/Other Information: Carcinogenicity.
 IARC Group 2A: Suspected human carcinogenic substance.
 NTP: Known to be human carcinogen Aluminum arsenide.
 OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. Additional studies are needed to determine whether the cell transforming activity of quartz is related to its carcinogenic potential. CAS# 64742-47-8: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 7732-18-5: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 2717-15-9: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 497-19-8: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 84133-50-6: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 64-02-8: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 25322-68-3: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 143-19-1: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 144-55-8: Not listed by ACGIH, IARC, NTP, or CA Prop 65.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
14808-60-7	Quartz {Silica-crystalline; Cistobalite; Tridymite}	Known	1	A2	n.a.
64742-47-8	Hydrotreated light distillate (petroleum)	n.a.	n.a.	A4	n.a.
2717-15-9	9-Octadecenoic acid (z)-, compd. with 2,2',2"-nitritotris[e	n.a.	n.a.	n.a.	n.a.

12. Ecological Information

General Ecological Information: Environmental: Biodegradable. Contains no phosphates or chromates.
 Physical: No information available.
 Other: Alcohol C6-17-secondary poly(3-6)ethoxylate is a marine pollutant.

Persistence and Degradability: No data available.

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

13. Disposal Considerations

Waste Disposal Method: Product.
 Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

Contaminated packaging.
 Dispose of as unused product. Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.
 RCRA P-Series: None listed.
 RCRA U-Series: None listed.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not Regulated. Not regulated as a hazardous material.
DOT Hazard Class:
UN/NA Number:

LAND TRANSPORT (Canadian TDG):

TDG Shipping Name: Not Regulated. Not regulated.

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
14808-60-7	Quartz {Silica-crystalline; Cistobalite; Tridymite}	No	No	No
64742-47-8	Hydrotreated light distillate (petroleum)	No	No	No
2717-15-9	9-Octadecenoic acid (z)-, compd. with 2,2',2"-nitrilotris[e	No	No	No

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
14808-60-7	Quartz {Silica-crystalline; Cistobalite; Tridymite}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
64742-47-8	Hydrotreated light distillate (petroleum)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
2717-15-9	9-Octadecenoic acid (z)-, compd. with 2,2',2"-nitrilotris[e	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No

16. Other Information

Revision Date: 07/09/2014
Preparer Name: Clifford Cantrell 678-296-1675
Additional Information About This Product:

**Company Policy or
Disclaimer:**

The information contained in this Material Safety Data Sheet is provided pursuant to current OSHA regulations to convey information concerning the hazardous nature of the

named product. The information supplied was compiled from the most reliable sources available at the time of preparation and in light of the most reasonable foreseeable exposure situations expected from the intended use of this product. The material(s) may present greater or lesser hazard exposure under other circumstances that are beyond the control of the manufacturer. Therefore it is imperative that all directions and warnings on the product label be read and closely followed.