

# Palmer SuperSet MIRRO-MASTIC®

## TECHNICAL INFORMATION

### 1. Product Name

Mirror Mastic: **SuperSet Mirro-Mastic®**

### 2. Manufacturer

Palmer Products Corporation

146 St. Matthews Ave.

Louisville, KY 40207

Phone: 800.431.6151

502.893.3668

Fax: 502.895.9253

Web site: [mirro-mastic.com](http://mirro-mastic.com)

E-mail: [palmer@mirro-mastic.com](mailto:palmer@mirro-mastic.com)

### 3. Product Description

**Basic Use:** Palmer SuperSet Mirro-Mastic is low VOC, solvent-free adhesive mastic formulated for adhering acrylic and glass mirror to various substrates such as drywall, wood, glass, metal or tile. VOC content of only 9 g/L qualifies SuperSet as LEED® Compliant.

### 4. Technical Data

**Composition and materials:** SuperSet is a one-component elastomeric hybrid sealant.

**Appearance:** Pasty

**Application temperature:** 59 to 95°F (15 to 35°C)

**Clean up:** Tools can be cleaned with methylethylketone(MEK) or acetone before full curing of the sealant. After curing, abrasion is necessary.

**Color:** White

**Coverage:** Approximately 20 square feet (1.9 square meters) per cartridge.

**Cure time:** >2 mm/24 h @ 73.4°F (23°C) and 50% HR

**Density:** 1.54 ± 0.05 @ 68°F (20°C)

**Flash point:** No Data Available

**Packaging:** 10.1 fl oz (300 ml) per cartridge (24 per case)

**VOC content:** 9 g/L - LEED® Compliant.

**Viscosity:** No data available

**Shelf life:** 10 months on an unopened cartridge.

**Storage:** Ideal storage 50°F to 85°F (10° to 29.4°C)

### WARNING

All Palmer products must be used only for approved purposes, and must be applied only in accordance with Palmer's installation instructions. The user bears all risk of damage, injury or other loss arising out of any nonapproved use and/or improper installation of any Palmer product. If Palmer's installation instructions are not followed, in whole or part, for whatever reason, then mechanical fasteners of sufficient size and strength must immediately be used to insure safety of the installation pending prompt proper reinstallation by the product user. Any failure to properly utilize or apply any Palmer product may result in property damage, bodily injury or death. Palmer shall not be responsible for these or any other types of misuse of its products.

