

1. PRODUCT AND COMPANY IDENTIFICATION

· **Product identifier**

Catalog Number: GN100A, GN100AS, GN101B

· **Trade name: 13793 Gunther Ultra Bond**

· **Article number: 13793**

· **Relevant identified uses of the substance or mixture. Sealant**

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Royal Adhesives And Sealants, LLC

2001 W. Washington Street

South Bend, IN 46628-2023

Information Phone Number: 574-246-5000

· **Information department: Environment protection department.**

· **Emergency telephone number:**

ChemTrec: Day or Night within USA and Canada: 1-800-424-9300.

Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2. HAZARDS IDENTIFICATION

· **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Eye Irrit. 2B H320 Causes eye irritation.

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

2. HAZARDS IDENTIFICATION (CONTINUED)

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word *Danger*

· Hazard statements

Highly flammable liquid and vapor.

Causes skin and eye irritation.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

If swallowed: Immediately call a poison center/doctor.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Do NOT induce vomiting.

In case of fire: Use for extinction: CO₂, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2

Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH	2	Health = 2
FIRE	2	Fire = 2
PHYSICAL HAZARD	0	Physical Hazard = 0

2. HAZARDS IDENTIFICATION (CONTINUED)

- *Other hazards*
- *Results of PBT and vPvB assessment*
- *PBT: Not applicable.*
- *vPvB: Not applicable.*

3. COMPOSITION / INFORMATION ON INGREDIENTS

- *Chemical characterization: Mixtures*
- *Description: Mixture*

- **Hazardous components:**

64741-84-0	Naphtha (petroleum), solvent-refined light	25-50%
67-64-1	acetone	2.5-10%
1330-20-7	xylene	2.5-10%
100-41-4	ethylbenzene	≤1.0%

4. FIRST AID MEASURES

- *Description of first aid measures*
- **After inhalation:**
Supply fresh air or oxygen; call for doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin becomes irritated seek medical attention.
- **After eye contact:**
Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment.
- **After swallowing:** Seek medical treatment.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5. FIRE FIGHTING MEASURES

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, sand, extinguishing powder. Do not use water.
Use fire fighting measures that suit the environment.
- **For safety reasons unsuitable extinguishing agents:** Water
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6. ACCIDENTAL RELEASE MEASURES

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

6. ACCIDENTAL RELEASE MEASURES (CONTINUED)

- **Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose of contaminated material as waste in accordance with federal state and local regulations.
 Ensure adequate ventilation.
- **Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7. HANDLING AND STORAGE

- **Handling:**
- **Precautions for safe handling**
 Avoid prolonged or repeated contact with skin.
 Avoid contact with eyes.
 Wash thoroughly after handling.
 Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
 Open containers in a well ventilated area and avoid breathing headspace vapors.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep container closed when not in use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location away from direct heat.
- **Information about storage in one common storage facility:**
 Store away from oxidizing agents.
 Store as flammable liquid.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· Components with limit values that require monitoring at the workplace:	
67-64-1 acetone	
PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm
	Long-term value: (1188) NIC-594 mg/m ³ , (500) NIC-250 ppm
	BEI
1330-20-7 xylene	
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm
	Long-term value: 435 mg/m ³ , 100 ppm

8. EXPOSURE CONTROLS / PERSONAL PROTECTION (CONTINUED)

TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
100-41-4 ethylbenzene	
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 87 mg/m ³ , 20 ppm BEI
· Ingredients with biological limit values:	
67-64-1 acetone	
BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
1330-20-7 xylene	
BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
100-41-4 ethylbenzene	
BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)
· Additional Occupational Exposure Limit Values for possible hazards during processing:	
110-54-3 n-hexane	
PEL	Long-term value: 1800 mg/m ³ , 500 ppm
REL	Long-term value: 180 mg/m ³ , 50 ppm
TLV	Long-term value: 176 mg/m ³ , 50 ppm Skin; BEI
110-82-7 cyclohexane	
PEL	Long-term value: 1050 mg/m ³ , 300 ppm
REL	Long-term value: 1050 mg/m ³ , 300 ppm
TLV	Long-term value: 344 mg/m ³ , 100 ppm
142-82-5 heptane	
PEL	Long-term value: 2000 mg/m ³ , 500 ppm
REL	Long-term value: 350 mg/m ³ , 85 ppm Ceiling limit value: 1800* mg/m ³ , 440* ppm *15-min
TLV	Short-term value: 2050 mg/m ³ , 500 ppm Long-term value: 1640 mg/m ³ , 400 ppm

8. EXPOSURE CONTROLS / PERSONAL PROTECTION (CONTINUED)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment (see listings below)**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
- **Breathing equipment:**
 Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**
 Nitrile rubber, NBR
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Safety glasses with side shields.
- **Body protection:** Protective work clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

· Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Paste
Color:	Tan
· Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point:	Undetermined.
Boiling point:	60° C (140° F)
· Flash point:	-17° C (1° F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	465.0° C (869° F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not self-igniting.

9. PHYSICAL AND CHEMICAL PROPERTIES (CONTINUED)

· Danger of explosion:	<i>Product is not explosive. However, formation of explosive air/vapor mixtures are possible.</i>
· Flammable limits: Lower: Upper:	<i>Not Determined Not Determined</i>
· Vapor pressure:	<i>Not determined.</i>
· Specific gravity: · Relative density · Vapour density · Evaporation rate	<i>1.02 Not determined. Not determined. Not determined.</i>
· Solubility in / Miscibility with Water:	<i>Not Soluble</i>
· Partition coefficient (n-octanol/water):	<i>Not determined.</i>
· Viscosity: Dynamic: Kinematic:	<i>Not determined. Not determined.</i>
· Solvent content: Organic solvents:	<i>30 - 50%</i>
Solids content: · Other information	<i>50 - 70% VOC = 3.1 LBS/GAL or 367 G/L SCAQMD = 386 G/L WEIGHT PER GALLON = 8.49 LBS/GAL</i>

10. STABILITY AND REACTIVITY

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *Heat, flames, sparks.*
- **Incompatible materials:** *Reacts with oxidizing agents.*
- **Hazardous decomposition products:** *Oxides of carbon and nitrogen under burning conditions.*

11. TOXICOLOGICAL INFORMATION

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
 - **on the skin:** *Irritant to skin and mucous membranes.*
 - **on the eye:**
 - Irritating effect.*
 - Vapors may be irritating to the eyes.*
- **Sensitization:** *No sensitizing effects known.*
- **Additional toxicological information:**
 - The product shows the following dangers according to internally approved calculation methods for preparations:*
 - Irritant*

11. TOXICOLOGICAL INFORMATION (CONTINUED)

· **Carcinogenicity categories**

· **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients are listed.

12. ECOLOGICAL INFORMATION


· **Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** At present there are no ecotoxicological assessments.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.




13. DISPOSAL CONSIDERATIONS

- **Waste treatment methods**
- **Recommendation:** Must be specially treated adhering to official regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14. TRANSPORT INFORMATION

· UN-Number · DOT, ADR, IMDG, IATA	UN1133
· UN proper shipping name · DOT, IMDG, IATA · ADR	ADHESIVES 1133 ADHESIVES, ENVIRONMENTALLY HAZARDOUS
· Transport hazard class(es) · DOT	
	
· Class	3 Flammable liquids

14. TRANSPORT INFORMATION (CONTINUED)

· Label	3
· ADR, IMDG	
 	
· Class	3 Flammable liquids
· Label	3
· IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	UN1133, ADHESIVES, ENVIRONMENTALLY HAZARDOUS, 3, II

15. REGULATORY INFORMATION

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
 · **Sara**

· Section 355 (extremely hazardous substances):	None of the ingredients are listed.
· Section 313 (Specific toxic chemical listings):	
1330-20-7	xylene
100-41-4	ethylbenzene
· TSCA (Toxic Substances Control Act):	All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.
· Proposition 65	
· Chemicals known to cause cancer:	
100-41-4	ethylbenzene
· Chemicals known to cause reproductive toxicity:	None of the ingredients are listed.
· (DSL) Canada Domestic Substance List	All components of this product are on the DSL (Canada Domestic Substance list) or are exempt from DSL requirements.

15. REGULATORY INFORMATION (CONTINUED)

- **Carcinogenicity categories**

· EPA (Environmental Protection Agency)		
67-64-1	acetone	I
1330-20-7	xylene	I
100-41-4	ethylbenzene	D
· TLV (Threshold Limit Value established by ACGIH)		
67-64-1	acetone	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
· MAK (German Maximum Workplace Concentration)		
100-41-4	ethylbenzene	3A
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
None of the ingredients are listed.		

- **National regulations:**

- **Water hazard class:** Water hazard class 3 (Self-assessment): extremely hazardous for water.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16. OTHER INFORMATION

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

- **Department issuing SDS:** Environment protection department.
- **Creation Date:** 07/16/2009
- **Date of preparation / last revision** 05/07/2015 / 3

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1