

CRL SIDELITE MOUNTED TRANSOM PATCH

North American 2 -3/4" (70mm) SetBack OR European 2 -9/16" (65mm) SetBack Cat No. PH40 Includes INT300 Insert, Cover Plates

Important Information:

measured from the "finished" door opening to the pivot center line. reverse the INT300 pivot insert to match either setback When using the PH40 Sidelite Mount Transom Patch simply 2 -3/4" (70mm) and 2 -9/16" (65mm) setbacks. This dimension is The PH40 Sidelite Mount Transom Patch is designed for

Specifications:

Glass Sizes: 3/8" (10mm) to 1/2" (12mm) thick tempered safety glass

Construction: High density casting

Cutout and Holes Required

Includes: Gaskets, screws and template

Insert: (Included) - INT300 Pivot Insert

Available Finishes:

Accessories: (Included) - None

- PH40A Satin Aluminum

- PH40BR Polished Brass (Lacquered)

- PH40BS Brushed Stainless Steel

- PH40PS Polished Stainless Steel

Use of Gaskets:

For 3/8" (10mm) Glass: Use two gaskets on each side For 1/2" (12mm) Glass: Use one gasket on each side

Cover Plates (Set of 2) Sold Separately

Recommendations:

safety glass For public safety, we recommend the use of only tempered

to Ensure Accuracy **Refer to Dimensions Shown** SEE TEMPLATE ON BACK