

# Mirro-Mastic® Bond

## Directions for Use:

1. Make sure that the substrate is free of dust, clean and dry. Never apply Bond or mastic to a painted surface.
2. Brush or roll Bond on the substrate and allow to dry.
3. For very porous substrates, two coats of Bond may be necessary. Allow the first coat to dry before applying the second.
4. Drying time is approximately one hour, but will depend on temperature, humidity, and type of substrate.
5. Allow drying time before applying mastic.
6. For technical questions not covered in our directions, please contact CRL Technical Sales (800) 421-6144, Ext. 777 or by e-mail at [techsales@crlaurence.com](mailto:techsales@crlaurence.com).

**Clean Up:** Mineral spirits

**Coverage:** One Gallon covers approximately 400 square feet, (37 square meters).

## **WARRANTY DISCLAIMER**

*Nothing herein shall be deemed to constitute a warranty, either express or implied by Palmer Products Corporation with respect to Mirro-Mastic® Bond or any other Palmer product. Palmer hereby disclaims all warranties, including without limitation, implied warranties of merchantability and fitness for a particular purpose. This disclaimer shall extend to all users of Palmer products and to any third party. Any dispute or claim of whatsoever type arising out of the use of any Palmer product shall be governed by the laws of the Commonwealth of Kentucky. Palmer's sole liability, if any, and any user's or third party claimant's sole and exclusive remedy relating to any such dispute or claim shall be replacement of the Palmer product used.*