

CRL BITUMINOUS COATING

DESCRIPTION

CRL Bituminous Coating is a low VOC cut-back asphalt of a thin brush, roll, or spray consistency. When applied, the material will be minimally tacky and exhibit a dark black color.

USAGE

CRL Bituminous Coating is used as a barrier to protect CRL Base Shoe, Posts, Railings, and Stanchions from electrolysis and corrosion when embedded in concrete. Simply brush on a clean and dry surface and allow to dry before embedding in concrete. For clean up use Cat. No. MEK1GL.

SURFACE PREPARATION

Be sure all substrates are dry, clean and free from oil, grease, rust scale, loose paint, dirt, dust, and debris that would interfere with surface contact and act as a bond breaker.

APPLICATION

This material is formulated to be of a brush, roller, or spray consistency. Coverage rates: approximately 100 to 200 sq. ft. per gallon, 33 sq. ft. per aerosol can on smooth surfaces. Surfaces with higher absorbency may yield lower coverage rates.

PACKAGING

5-gallon pails (net contents 4.7 gallons [17.8 l]) and 15 ounce (425 g) aerosol cans.

APPEARANCE	Glossy black, thin material
BROOKFIELD VISCOSITY	<3000
% SOLIDS BY WEIGHT	63-65
FLASH POINT	>105°F
VOC CONTENT: G/L	<350 g/L (pails), 487 g/L (aerosol cans)
WEIGHT PER GALLON	7.5-7.9
DRY TO TOUCH TIME @ 72°F	45 minutes (pails), 10 minutes (aerosol cans)

Note: The information contained in this data sheet is believed to be reliable. C.R. LAURENCE CO., INC. makes no representation or warranties of any kind concerning this information. It is the user's responsibility to determine the suitability of this product for any intended use. The user assumes all risk and liability connected with the use of this product.