GRS GATE SYSTEMS



Cap Railing Swinging Gate Quote/Order Request Form Date _____

Name	
Email	
Phone	Number

Company _ Account Number Job Name


Utilize this form to assist you in covering the details required to quote the Cap Railing Swinging Gate System. Going through this exercise should prevent you from overlooking any details related to your installation.


IMPORTANT: Depending on the complexity of your project, one or more of the following may be required to accurately order: sketches or drawings of your particular application with dimensions; printed architectural drawings or CAD files; photos of the job site conditions (digital images are preferable).


NOTE: Please download and submit completed form to railings.archmetals@crlaurence.com. A final sign off is required prior to any custom fabrication.

Wall Mounted (Type W#) and Post Mounted (Type P#) Gates

These are the most common configurations of Swinging Gates. Find the configuration that best matches your requirements and then use the handy menu on the next page to design the Swinging Gate that's right for you.








TYPES W1/P1 Wall or post mount top pivot, floor closer, cap rail, top patch, and full bottom rail.


TYPES W2/P2 Wall or post mount top pivot, floor closer, cap rail, top and bottom patch.


TYPES W3/P3 Wall or post mount top pivot, floor closer, top patch, and full bottom rail.

TYPES W4/P4 Wall or post mount top pivot, floor closer, top and bottom patch.



TYPES W6/P6 Wall or post mount top and





TYPES W5/P5 Wall or post mount top and bottom pivots, cap rail, top patch, and full bottom rail.

bottom pivots, cap rail, top and bottom patch.

TYPES W7/P7 Wall or post mount top and bottom pivots, top patch, and full bottom rail.

TYPES W8/P8 Wall or post mount top and bottom pivots, top and bottom patch.

NOTE: We recommend the use of 1/2" (12 mm), 5/8" (16 mm), or 3/4" (19 mm) tempered monolithic or tempered laminated glass.

RESET BUTTON

Please submit to: railings.archmetals@crlaurence.com





Cap Railing Swinging Gate Quote/Order Request Form

WALL MOUNT SWINGING GATE WITH

CAT. NO.	TOP PIVOT PLUS	TYPE				
SGW1C SGW2C SGW3C SGW4C	Cap Rail, Top Patch, and Full Bottom Rail Cap Rail, Top and Bottom Patch Top Patch and Full Bottom Rail Top and Bottom Patch	W1 W2 W3 W4				
CAT. NO.	TOP AND BOTTOM PIVOT PLUS	TYPE				
SGW5C SGW6C SGW7C SGW8C	Cap Rail, Top Patch, and Full Bottom Rail Cap Rail, Top and Bottom Patch Top Patch and Full Bottom Rail Top and Bottom Patch	W1 W2 W3 W4				

POST MOUNT SWINGING GATE WITH

CAT. NO.	TOP PIVOT PLUS	TYPE
SGP1C SGP2C SGP3C SGP4C	Cap Rail, Top Patch, and Full Bottom Rail Cap Rail, Top and Bottom Patch Top Patch and Full Bottom Rail Top and Bottom Patch	P1 P2 P3 P4
CAT. NO.	TOP AND BOTTOM PIVOT PLUS	TYPE
SGP5C	Cap Rail, Top Patch, and Full Bottom Rail	P5
SGP5C	Cap Rail, Top Patch, and Full Bottom Rail	P5

NOTE: We recommend the use of 1/2" (12 mm), 5/8" (16 mm), or 3/4" (19 mm) tempered monolithic or tempered laminated glass.

SELECT GATE STYLE		FLOOR CLOSER/	POST SIZE	BOTTOM RAIL STYLE
Wall Mount W1 W2 W3 W4 W5 W6 W7 W8	Post Mount P1 P2 P3 P4 P5 P6 P7 P8	FLOOR CLOSERY FLOOR PIVOT OPTIONS J990NHOD 180 Degree Swing No Hold Open J993HOD 180 Degree Swing Hold Open CRL8010DP Floor/Threshold Mnt. Pivot CRL8010BP Standard Floor Mnt. Pivot Other	Round Post	4" (101.6 mm) Tall (Wide Style) Bottom Rail 4" (101.6 mm) Standard Bottom Rail 9-1/2" (241 mm) Long Patch Fitting
BOTTOM RAIL	LOCK OPTIONS	POST MOUNT	HANDING	
 None Cylinder Both Sides Cylinder (Outside Only) Cylinder (Inside Only) Cylinder/Thumbturn (Outside) Cylinder/Thumbturn (Inside) Other 		☐ Core Mount ☐ Surface Mount with Base Plate ☐ Other	Left Hand (LH) Inside Outside	
CENTER LOCK	HOUSINGS	GLAZING		1
☐ PTH311 Glass Mounted Latch Lock ☐ PTH312 ☐ PTH314 ☐ PTH303		☐ 1/2" (12 mm) ☐ 5/8" (16 mm) ☐ 3/4" (19 mm) ☐ Other		Inside Right Hand (RH) Outside
□ None			Left Hand Reverse (LHR)	
FINISH		TOP CAP DIAMETER	Inside	
Brushed Stain Polished Stain Polished Brass Satin Brass (Some Satin Anodized Dark Bronzed Powder Coated Custom Finis	nless Steel (PS) ss (PB) sB) ed (SA) Anodized (DU) sed (PT) RAL#	□ 1-1/2" (38.1 mm) Diameter Top Cap □ 2" (50.8 mm) Diameter Top Cap □ 2-1/2" (63.5 mm) Diameter Top Cap □ 3" (76.2 mm) Diameter Top Cap □ 3-1/2" (88.9 mm) Diameter Top Cap □ 4" (101.6 mm) Diameter Top Cap □ 1-1/2" (38.1 mm) Square Top Cap □ 2" (50.8 mm) Square Top Cap □ 2-1/2" (63.5 mm) Square Top Cap	Outside	Right Hand Reverse (RHR) Inside Outside
		☐ No Cap		Please submit to:

RESET BUTTON

Please submit to: railings.archmetals@crlaurence.com

