



- Notes:**
- Do not scale drawing.
  - Left hand door shown from Push Side.
  - All dimensions are given in inches and millimeters (mm).
  - This template information based upon use of 5" (127 mm) maximum width butt hinges or 3/4" (19 mm) offset pivots.
  - Ceiling clearance of 5-1/4" (133 mm) from frame rabbet is required for this application.
  - Frame reveal range for this application is 3" (76 mm) to 7" (178 mm) for this application.
  - Conduit hole nearest hinge is suggested for 120 VAC power input.
  - Thickness recommended for reinforcements in hollow-metal doors and frames should provide a combined material thickness of .164" (4.2 mm) MIN.

Door Opening Angle	Dim "A"	Dim "B"
Up to 110°	12 (305)	15-3/4 (400)
111° to 170°	9-1/2 (241)	13-1/4 (337)

**Series 5730 LEO™ – Door Openings 85° to 110° or 111° to 180°  
 Double Lever Arm Application for Frame Reveals 3" (76) to 7" (178mm)  
 Stop (Push) Side of Door Installation**

**Norton®**  
**Norton Door Controls**  
[www.nortondoortcontrols.com](http://www.nortondoortcontrols.com)  
 TEMPLATE NUMBER: **7357-0130 Rev A**      DATE: **10-04**