

## MATERIAL SAFETY DATA SHEET

**Company Name:** SHERWIN-WILLIAMS  
**Address:** 31500 SOLON RD  
**City / State / Zip:** SOLON / OH / 44139  
**US-CHEMTREC Phone(I):** (800)424-9300  
**US-CHEMTREC Phone(II):** (703)527-3887  
**CAN-CANUTEC Phone:** (613)996-6666  
**Vendor Update:** 11/27/2009  
**Date Prepared:** 1/26/2010  
**MSDS Number:** KP1501 ;

### I. CHEMICAL PRODUCT IDENTIFICATION

**Product Name:** KRYLON TOUCH UP SPRAY – GLOSSY WHITE  
**HMIS Ratings:**

Health: Moderate(2)  
 Flammability: Serious(3)  
 Instability/Reactivity: Minimal(0)

**NFPA Ratings:**

### II. COMPOSITION, INFORMATION ON INGREDIENTS

| Chemical Ingredients         | C.A.S. Number | % By Weight | ACGIH TLV TWA/STEL           | OSHA PEL TWA/STEL  | Other TWA/STEL | LD50                   | LC50                  |
|------------------------------|---------------|-------------|------------------------------|--|----------------|------------------------|-----------------------|
| PROPANE                      | 74-98-6       | 14          | 2500 PPM                     | 1000 PPM   |                |                        |                       |
| Notes                        |               |             |                              |  |                |                        |                       |
| BUTANE                       | 106-97-8      | 6           | 800 PPM                      | 800 PPM  |                |                        |                       |
| Notes                        |               |             |                              |  |                |                        |                       |
| ETHYL BENZENE                | 100-41-4      | 1           | 100 PPM<br>125 PPM           | 100 PPM<br>125 PPM   |                | RAT 4HR:<br>3500 MG/KG |                       |
| Notes                        |               |             |                              |  |                |                        |                       |
| XYLENE                       | 1330-20-7     | 7           | 100 PPM<br>150 PPM           | 100 PPM<br>150 PPM   |                | RAT 4HR:<br>4300 MG/KG | RAT 4 HR:<br>5000 PPM |
| Notes                        |               |             |                              |  |                |                        |                       |
| ACETONE                      | 67-64-1       | 36          | 500PPM<br>750 PPM            | 1000 PPM   |                | RAT 4HR:<br>5800 MG/KG |                       |
| Notes                        |               |             |                              |  |                |                        |                       |
| METHYL ETHYL KETONE          | 78-93-3       | 14          | 200 PPM<br>300 PPM           | 200 PPM<br>300 PPM   |                | RAT 4HR:<br>2740 MG/KG |                       |
| Notes                        |               |             |                              |  |                |                        |                       |
| 1-METHOXY-2-PROPANOL ACETATE | 108-65-6      | 6           |                              |  |                | RAT 4HR:<br>8500 MG/KG |                       |
| Notes                        |               |             |                              |  |                |                        |                       |
| TITANIUM DIOXIDE             | 13463-67-7    | 6           | 10 MG/M <sup>3</sup> AS DUST | 10 MG/M <sup>3</sup> AS DUST;<br>5 MG/M <sup>3</sup> RESPIRABLE FRACTION |                |                        |                       |
| Notes                        |               |             |                              |  |                |                        |                       |

### III. HAZARDS IDENTIFICATION PRIMARY ROUTE OF ENTRY

**Eyes:** IRRITATION

**Skin:** PROLONGED OR REPEATED EXPOSURE MAY CAUSE IRRITATION.

**Inhalation:** IRRITATION OF THE UPPER RESPIRATORY SYSTEM.

|  |  |
|--|--|
| <b>Signs and Symptoms of Exposure:</b> | MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE MAY RESULT IN UNCONSCIOUSNESS AND POSSIBLY DEATH. PROLONGED OVEREXPOSURE TO SOLVENT INGREDIENTS IN SECTION II MAY CAUSE ADVERSE EFFECTS TO THE LIVER, URINARY, CARDIOVASCULAR, AND REPRODUCTIVE SYSTEMS.<br>SIGNS/SYMPTOMS OF OVEREXPOSURE:<br>HEADACHE, DIZZINESS, NAUSEA, AND LOSS OF COORDINATION ARE INDICATIONS OF EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MISTS. REDNESS AND ITCHING OR BURNING SENSATION MAY INDICATE EYE OR EXCESSIVE SKIN EXPOSURE. |
| <b>Other:</b>                          | ROUTES OF EXPOSURE:<br>INHALATION OF VAPOR OR SPRAY MIST.<br>EYE OR SKIN CONTACT WITH THE PRODUCT, VAPOR OR SPRAY MIST.  |

#### IV. FIRST AID MEASURES

|                    |  |
|--------------------|--|
| <b>Eyes:</b>       | FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.                              |
| <b>Skin:</b>       | WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE RE-USE. |
| <b>Ingestion:</b>  | DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.   |
| <b>Inhalation:</b> | IF AFFECTED, REMOVED FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET.                                |

#### V. FIRE FIGHTING MEASURES

|   |  |
|---|--|
| <b>Flash Point:</b>                       | PROPELLANT <0° F   |
| <b>Lower Flammability Limit:</b>          | 1.0  |
| <b>Upper Flammability Limit:</b>          | 13.1   |
| <b>Extinguishing Agents:</b>              | CARBON DIOXIDE, DRY CHEMICAL, FOAM   |
| <b>Unusual Fire or Explosion Hazards:</b> | CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS. DURING EMERGENCY CONDITIONS OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION.                                   |
| <b>Fire Fighting Procedures:</b>          | FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. |

#### VI. ACCIDENTAL RELEASE MEASURES

|                             |  |
|-----------------------------|--|
| <b>Containment/Cleanup:</b> | REMOVE ALL SOURCES OF IGNITION. VENTILATE THE AREA. REMOVE WITH INERT ABSORBENT. |
|-----------------------------|--|

#### VII. HANDLING AND STORAGE

|               |  |
|---------------|--|
| <b>Other:</b> | KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. VAPORS WILL ACCUMULATE READILY AND MAY IGNITE EXPLOSIVELY. DURING USE AND UNTIL ALL VAPORS ARE GONE: KEEP AREA VENTILATED –DO NOT SMOKE– EXTINGUISH ALL FLAMES, PILOT LIGHTS, AND HEATERS– TURN OFF STOVES, |
|---------------|--|

ELECTRIC TOOLS AND APPLIANCES AND ANY OTHER SOURCES OF IGNITION. CONSULT NFPA CODE. USE APPROVED BONDING AND GROUNDING PROCEDURES. CONTENTS UNDER PRESSURE. DO NOT PUNCTURE, INCINERATE, OR EXPOSE TO TEMPERATURE ABOVE 120°F. HEAT FROM SUNLIGHT, RADIATORS, STOVES, HOT WATER, AND OTHER HEAT SOURCES COULD CAUSE CONTAINER TO BURST. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

#### VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

|                     |  |
|---------------------|--|
| <b>Eyes:</b>        | WEAR SAFETY SPECTACLES WITH UNPERFORATED SIDESHIELDS.  |
| <b>Skin:</b>        | PROTECTIVE GLOVES: NONE REQUIRED FOR NORMAL APPLICATION OF AEROSOL PRODUCTS WHERE MINIMAL SKIN CONTACT IS EXPECTED. FOR LONG OR REPEATED CONTACT, WEAR CHEMICAL RESISTANT GLOVES.  |
| <b>Respiratory:</b> | IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA FOR PROTECTION AGAINST MATERIALS IN SECTION II. WHEN SANDING, OR ABRADING THE DRIED FILM, WEAR A DUST/MIST RESPIRATOR APPROVED BY NIOSH/MSHA FOR DUST WHICH MAY BE GENERATED FROM THIS PRODUCT, UNDERLYING PAINT, OR THE ABRASIVE.  |
| <b>Engineering:</b> | VENTILATION:<br>LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF THE EXPOSURE TO MATERIALS IN SECTION II IS MAINTAINED BELOW APPLICABLE EXPOSURE LIMITS. REFER TO OSHA STANDARDS 1910.94, 1910.107, 1910.108.   |
| <b>Other:</b>       | PRECAUTIONS TO BE TAKEN IN USE:<br>USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR AND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES. WASH HANDS AFTER USING. THIS COATINGS MAY CONTAIN MATERIALS CLASSIFIED AS NUISANCE PARTICULATES (LISTED "AS DUST" IN SECTION II) WHICH MAY BE PRESENT AT HAZARDOUS LEVELS ONLY DURING SANDING OR ABRADING OF THE DRIED FILM. IF NO SPECIFIC DUSTS ARE LISTED IN SECTION II, THE APPLICABLE LIMITS FOR NUISANCE DUSTS ARE ACGIH TLV 10 MG/M <sup>3</sup> (TOTAL DUST), 3 MG/M <sup>3</sup> (RESPIRABLE FRACTION). OSHA PEL 15 MG/M <sup>3</sup> (TOTAL DUST), 5 MG/M <sup>3</sup> (RESPIRABLE FRACTION).<br>OTHER PRECAUTIONS:<br>INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENT CAN BE HARMFUL OR FATAL. |

#### IX. PHYSICAL AND CHEMICAL PROPERTIES

|                             |   |
|-----------------------------|---|
| <b>Appearance:</b>          | GLOSSY WHITE  |
| <b>Boiling Point:</b>       | <0 – 302° F (<-18 – 150°C)  |
| <b>pH:</b>                  | 7.0   |
| <b>Solubility in Water:</b> | NOT APPLICABLE  |
| <b>Specific Gravity:</b>    | 0.79  |
| <b>Vapor Pressure:</b>      | *   |
| <b>Vapor Density:</b>       | HEAVIER THAN AIR  |
| <b>Volatile Content:</b>    | VOLATILE VOLUME 92%<br>VOLATILE ORGANIC COMPOUNDS (VOC THEORETICAL– AS PACKAGED)<br>VOLATILE WEIGHT 48.81%; LESS WATER & FEDERALLY EXEMPT SOLVENTS                  |
| <b>Other:</b>               | PRODUCT WEIGHT: 6.58 LBS/G (788 G/L)<br>MELTING POINT: NOT AVAILABLE<br>EVAPORATION RATE: FASTER THAN ETHER<br>*VAPOR PRESSURE<br>PROPANE: 760 MM<br>BUTANE: 760 MM |

ETHYLBENZENE: 7.1 MM  
 XYLENE: 5.9 MM  
 ACETONE: 180 MM  
 METHYL ETHYL KETONE: 70 MM  
 1-METHOXY-2-PROPANOL ACETATE: 1.8 MM

#### X. STABILITY AND REACTIVITY

**Stability:** STABLE

**Hazardous Polymerization:** WILL NOT OCCUR

**Hazardous Decomposition** BY FIRE: CARBON DIOXIDE, CARBON MONOXIDE

**Products:**

**Incompatible Products:** NONE KNOWN

**Conditions To Avoid:** NONE KNOWN

#### XI. TOXICOLOGICAL INFORMATION

**Other:** CHRONIC HEALTH HAZARDS:  
 METHYL ETHYL KETONE MAY INCREASE THE NERVOUS SYSTEM EFFECTS OF OTHER SOLVENTS.  
 REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. ETHYLBENZENE IS CLASSIFIED BY IARC AS POSSIBLY CARCINOGENIC TO HUMANS (2B) BASED ON INADEQUATE EVIDENCE IN HUMANS AND SUFFICIENT EVIDENCE IN LABORATORY ANIMALS. LIFETIME INHALATION EXPOSURE OF RATS AND MICE TO HIGH ETHYLBENZENE CONCENTRATIONS RESULTED IN INCREASED IN CERTAIN TYPES OF CANCER, INCLUDING KIDNEY TUMORS IN RATS AND LUNG AND LIVER TUMORS IN MICE. THESE EFFECTS WERE NOT OBSERVED IN ANIMALS EXPOSED TO LOWER CONCENTRATIONS. THERE IS NO EVIDENCE THAT ETHYLBENZENE CAUSES CANCER IN HUMANS. IARC'S MONOGRAPH NO. 93 REPORTS THERE IS SUFFICIENT EVIDENCE OF CARCINOGENICITY IN EXPERIMENTAL RATS EXPOSED TO TITANIUM DIOXIDE BUT INADEQUATE EVIDENCE FOR CARCINOGENICITY IN HUMANS AND HAS ASSIGNED A GROUP 2B RATING. IN ADDITION, THE IARC SUMMARY CONCLUDES, "NO SIGNIFICANT EXPOSURE TO TITANIUM DIOXIDE IS THOUGHT TO OCCUR DURING THE USE OF PRODUCTS IN WHICH TITANIUM IS BOUND TO OTHER MATERIALS, SUCH AS PAINT."

#### XII. ECOLOGICAL INFORMATION

**Environmental Fate and** NO DATA AVAILABLE

**Distribution:**

#### XIII. DISPOSAL CONSIDERATIONS

**Disposal Method:** WASTE FROM THIS PRODUCT MAY BE HAZARDOUS AS DEFINED UNDER THE RESOURCE CONSERVATION AND RECOVERY ACT (RCRA) 40 CFR 261. WASTE MUST BE TESTED FOR IGNITABILITY TO DETERMINE THE APPLICABLE EPA HAZARDOUS WASTE NUMBERS.  
 DO NOT INCINERATE. DEPRESSURIZE CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE/PROVINCIAL AND LOCAL REGULATIONS REGARDING POLLUTION.

#### XIV. TRANSPORT INFORMATION

**DOT Label(s) Required:** MAY BE CLASSED AS CONSUMER COMMODITY, ORM-D, UN1950, AEROSOLS, 2.1, LIMITED QUANTITY, (ERG#126)

**Canada:** MAY BE CLASSED AS CONSUMER COMMODITY, ORM-D.  
**UN Identification Number:** UN1950, AEROSOLS, CLASS 2.1, LIMITED QUANTITY, (ERG#126)  
**Label(s):** MAY BE SHIPPED AS LIMITED QUANTITY. UN1950, AEROSOLS, CLASS 2.1, LIMITED QUANTITY, EMS F-D, S-U

**XV. REGULATORY INFORMATION**

**TSCA Status:** ALL CHEMICALS IN THESE PRODUCTS ARE LISTED, OR ARE EXEMPT FROM LISTING, ON THE TSCA INVENTORY.

**EPA Sara Title III Chemical Listings:** SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

ETHYLBENZENE: CAS#: 100-41-4; % BY WT: 1

XYLENE: CAS# 1330-20-7; % BY WT: 7.

**California:** PROP 65 WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

**XVI. OTHER INFORMATION**

**Other:** THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CANADIAN CONTROLLED PRODUCTS REGULATIONS (CPR) AND THE MSDS CONTAINS ALL OF THE INFORMATION REQUIRED BY THE CPR.

**WARRANTY INFORMATION**

THIS INFORMATION IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.