


COMPANY NAME _____	PHONE _____
CONTACT _____ ACCOUNT NO. _____	FAX _____
JOB NAME _____	EMAIL _____

☐ **QUOTE** ☐ **ORDER P.O. #** _____ **DATE** _____

STANDARD PROFILE DIMENSIONS				
SERIES	THICKNESS	STILE	TOP RAIL	BOTTOM RAIL
550T WIDE STILE THERMAL DOOR	1-3/4"	5-1/2"	6"	7-1/4"
550AT WIDE STILE ADVANCE THERMAL DOOR	1-3/4"	5-1/2" (Foam Filled)	6" (Foam Filled)	7-1/4" (Foam Filled)
OPTIONAL				10"



Use the Door Swing Chart to determine how the door(s) should be handed.

APPLICATION : HEAVY TRAFFIC

DOOR STILE	APPLICATION
☐ 550T Wide Stile Thermal Door	
☐ 550AT Wide Stile Advance Thermal Door	

DOOR FINISH
☐ 11 - Clear Anodized Class I
☐ 22 - Dark Bronze / Black Anodized Class I
☐ 52 - Bone White 70% KYNAR® (2-Coat)
☐ 71 - Standard 70% KYNAR® (2-Coat) Standard Color per Chart- Specify _____
☐ 71 - Custom 70% KYNAR® (2-Coat) - Specify _____
☐ 71 - Custom 70%KYNAR®(3-Coat) - Specify _____

DOOR HINGING
☐ Top/Bottom and Intermediate Offset Pivots (OP500/DH010)
• Additional Pivot ☐ DH010 Add _____ per Door
☐ 1-1/2 Pair Butt Hinges (DH009)
☐ Additional Butt Hinge Add _____ per Door
☐ Continuous Geared Hinge (DH492)
☐ By USALUM
☐ By Customer
☐ Prep and Supply
☐ Prep Only (Selection Above)
☐ No Prep

DOOR OPENING SIZE
☐ 36" x 84"
☐ Custom Single _____ Door Tag # _____
☐ 72" x 84"
☐ Custom Pair _____ Door Tag # _____
Maximum Leaf Size 48" x 96"

GLASS STOP
1" (25 mm) Square Glass Stops

TOP RAIL - INCLUDES GLASS STOP
☐ 6" WT201 (Standard)
☐ 2-7/8" HT201
☐ 4-5/16" HT101
☐ Custom _____

BOTTOM RAIL - INCLUDES GLASS STOP
☐ 7-1/4" JT650 (Standard)
☐ 4-5/16" HT101
☐ 6" WT201
☐ 10" WT196

MUNTINS - INCLUDES GLASS STOP
☐ 3-5/8" (HT202)
☐ 5-1/16" (MT101)
☐ 6-3/4" (MT201)
☐ 8" (JT650)
☐ 10-3/4" (MT196)

HARDWARE FINISH	DOOR FINISH
• Clear	11, 12, 52, 71
• Bronze	22
☐ Specify _____	

DOOR SWEEP
☐ Yes ☐ No
☐ Exposed Fasteners
☐ Concealed Fasteners

DOOR SWING	QTY
☐ LHR Hinge Left Swing Out	_____ ea.
☐ RHR Hinge Right Swing Out	_____ ea.
☐ LH Hinge Left Swing In	_____ ea.
☐ RH Hinge Right Swing In	_____ ea.
☐ PAIR Swing In	_____ ea.
☐ PAIR Swing Out	_____ ea.

LOCKING OPTIONS
☐ MS Hookbolt With Two Cylinders - STD
☐ Long Throw Deadlock With Cylinders
☐ 3-Point Locking @ Pair With Cylinders
☐ Latch/Deadlock (DH189) With Cylinders
☐ Thumbturn in Lieu of Cylinder
☐ Latchlock (DH002)
☐ Cylinder (Ext.) ☐ Cylinder (Int.)
☐ Thumbturn (Int.)
☐ Lock Indicator
☐ Cylinder Guard
☐ Flushbolts (DH008)
☐ Paddle Handle
• DH569 Lever Handle
☐ Interior ☐ Back to Back
• CRL DL2150 Lever Handle
☐ Interior ☐ Back to Back
☐ Electric Strike
☐ Prep and Supply ☐ Prep Only

PANIC DEVICES
☐ Jackson 1285 Concealed Vertical Rod Panic
☐ Jackson 1295 Rim Panic Device
☐ Jackson 2086 Concealed Vertical Rod Panic
☐ Jackson 2095 Rim Panic Device
☐ Jackson 1085 Concealed Vertical Rod Panic
☐ Jackson 1095 Rim Panic Device
☐ Adams-Rite 8400 Mortise Panic Device
☐ Adams-Rite 8600 Concealed Vertical Rod Panic
☐ Adams-Rite 8800 Rim Panic Device
☐ with cylinder ☐ cylinder by others (prep only)
☐ Von Duprin® 33AE ☐ Von Duprin® 35AE
☐ Von Duprin® 3327AE ☐ Von Duprin® 3527AE
☐ Von Duprin® 3347AE ☐ Von Duprin® 3547AE
• Outside Von Duprin Trim
☐ 360L ☐ 360T ☐ 388NL
☐ with cylinder ☐ cylinder by others (prep only)
☐ Exit Only
☐ By USALUM ☐ By Customer
☐ Prep and Supply
☐ Prep Only (Selection Above)

FOR OFFICE USE ONLY
TAKEN BY: _____
PRICED BY: _____
EDITED BY: _____

PUSH/PULL HARDWARE

- ☐ Standard Push/Pull
☐ Offset Pulls
☐ None _____
☐ Custom ☐ By USALUM ☐ By Customer
☐ Prep and Supply ☐ Prep Only

NOTE: Prep Only Requires Manufacturer's

Name , Model, and Template

Manufacturer: _____

Model: _____

DOOR CLOSER

- ☐ O.H. Concealed (Offset-Prep Only)
☐ Standard Jackson Closer (Supply)
☐ 90° ☐ 105° Hold Open ☐ Yes ☐ No
☐ CRL Surface Mount Closer (Supply)
☐ Drop Plate
☐ Door Stop/Holder Degree _____
☐ No Closer Required
☐ Custom ☐ By USALUM ☐ By Customer
☐ Prep and Supply ☐ Prep Only

NOTE: Prep Only Requires Manufacturer's Name ,

Model, and Template

Manufacturer: _____

Model: _____

BLUMCRAFT PANIC DEVICES

- ☐ PA100 ☐ PA110
- Blumcraft Electric Strike
 - YES ☐ Folger Adam 310-1 with 3/4" Straight Keeper (FA3101-24V DC)
 - NO ☐ Without Signal Switch
 - Furnish by CRL
- Exterior Blumcraft Pull
 - ☐ D ☐ F ☐ J-S ☐ L-S ☐ Z (None)
- Exterior Blumcraft Cylinder
 - ☐ Exterior Key Cylinder
 - ☐ No Exterior Key Cylinder
- Blumcraft Hardware Finishes
 - ☐ Stainless Steel
 - ☐ #4 Satin ☐ #8 Polish
 - ☐ Brass
 - ☐ #4 Satin ☐ #8 Polish
 - ☐ Oil Rubbed Bronze

FRAME SYSTEM

Series IT451 2" x 4-1/2" ☐ Open Back
Subframe ☐ 1" x 4-1/2" (Thermal) Tubular Only

FRAME TYPE

- ☐ Up and Over (No Transom)
- ☐ 126" (3.2 m) High With Transom
- ☐ Frame Only
- ☐ Door Only (No Frame)
- ☐ Custom

CLEARANCES/THRESHOLD

Clearance from Bottom of Door to Finish Floor

- ☐ 11/16" Standard (Required for 0P500 Pivot Set)
- ☐ Custom Clearance
- Specify _____

- TT245 1/2" Threshold

ADDITIONAL NOTES OR SKETCHES

FOR OFFICE USE ONLY

TAKEN BY: _____

PRICED BY:

EDITED BY:

APPROVED BY _____ DATE _____

NOTE: PLEASE DOWNLOAD FORM TO SUBMIT. DO NOT FILL FORM ONLINE.

Email completed form to usalum@crlaurence.com.

Fax checklist to U.S. Aluminum Technical Sales at (877) 883-7547

To review call (800) 627-6440. This form is available online at usalum.com.