




**C.R. LAURENCE CO., INC.**  
PROFESSIONAL QUALITY



**\* SEE TEMPLATE ON BACK \***  
Refer to Dimensions Shown  
to Ensure Accuracy

# PINNACLE

## Adjustable Wall Mount Hinge

### CAT. No. PIN337/PIN344

*Maximum Door Capacities	3/8" (10mm) Glass Weight	3/8" (10mm) Glass Width	1/2" (12mm) Glass Weight	1/2" (12mm) Glass Width
Using 2 Hinges	80 lbs.(36 kg)	28"(711mm)	80 lbs.(36 kg)	28"(711mm)
Using 3 Hinges	120 lbs.(55 kg)	32"(813mm)	120 lbs.(55 kg)	32"(813mm)

**\*NOTE:** Do not exceed either maximum weight or width when choosing proper quantity of hinges.

## Important Information:

This hinge adjusts to accommodate the desired door closing position up to 90°, after the door is installed. This is achieved by loosening the Allen set screws (located on the rear of the center block), moving the door to the desired closing position, and then tightening the screws. The self-centering position has now been changed to the angle you desire.

## Specifications:

**Glass Sizes:** 3/8" (10mm) to 1/2" (12mm) thick tempered safety glass  
**Construction:** Solid brass  
**Closing Type:** Self-centering when within 15° of closing position  
**Cutout Required**  
**Includes:** Gaskets, screws and template

## Use of Gaskets:

**For 3/8"(10mm) Glass:** Use one thick gasket on each side  
**For 1/2"(12mm) Glass:** Use one thin gasket on each side

## Recommendations:


For public safety, we recommend the use of only tempered safety glass. Do not use power tools when installing these hinges.

## Maintenance Guidelines:

- Our hinges are greased at the factory for quiet and trouble-free operation. If there is any squeaking that occurs after installation, put a drop of "3 in 1 Oil" (also known as "household oil") on the white nylon washer that the hinge body pivots on. This washer is the component that acts as a buffer, so the body of the hinge doesn't pivot directly on the brass center block. This solution doesn't require the disassembly of the hinge.  
**Note: Do not use spray lubricant on these hinges.** If the hinge has been disassembled, upon re-assembly, use white lithium grease to lubricate the interior mechanism.
- Never use an abrasive cleaner on the hardware. Many of the components are coated with a clear lacquer that will be irreparably damaged if subjected to harsh, abrasive chemicals. Advise your customer that drying the hardware with a clean, soft towel on a daily basis is the best way to maintain the hardware. If mineral deposits build-up, mix a couple of drops of a mild liquid soap (such as Ivory or a similar product) into a cup of warm water. Using a soft, non-abrasive cloth, clean the hardware. Rinse thoroughly with clean, warm water and dry.



**C.R. LAURENCE CO., INC.**  
PROFESSIONAL QUALITY



# PINNACLE

Adjustable Wall Mount Hinge

**CAT. No. PIN337/PIN344**

