

COMPANY NAME _____	PHONE _____
CONTACT _____ ACCOUNT NO. _____	FAX _____
JOB NAME _____	EMAIL _____

☐ **QUOTE**
 ☐ **ORDER P.O. #** _____ **DATE** _____

CAT. NO.	RATING	MAXIMUM SIZE	MINIMUM SIZE
☐ TV201 Project-Out Bottom Vent (Awning)	CW-PG75	60" X 32"	15" X 15"
☐ TV204 Project-In Top Vent (Hopper)	CW-PG75	60" X 32"	15" X 15"
☐ TV205 Fixed	CW-PG90	72" X 72"	15" X 15"
☐ TV206 Out-Swing Casement ☐ HLSO ☐ HRSO	CW-PG75-C	30" X 60"	15" X 15"
☐ TV226 Double Out-Swing Casement	VARIES	60" X 60"	30" X 30"
☐ TV220 Dual Bay Vertical Stacked Window	VARIES	Varies	Varies
☐ TV230 Triple Bay Vertical Stacked Window	VARIES	Varies	Varies

FINISHES		
☐ 11 - Clear Anodized Class I ☐ 22 - Dark Bronze / Black Anodized Class I	☐ 52 - Bone White 70% KYNAR® (2-Coat) ☐ 71 - Standard 70% KYNAR® (2-Coat) Standard Color per Chart - Specify _____	☐ 71 - Custom 70% KYNAR® (2-Coat) Specify _____ ☐ 71 - Custom 70% KYNAR® (3-Coat) Specify _____

GLAZING THICKNESS (NOT INCLUDED)
☐ 1/4" (6 mm) ☐ 1" (25 mm)

STANDARD HARDWARE
• 60 Degree Stainless Steel 4-Bar Hinge • WH240 - Cam Handle Lock / Brushed Nickel Option ☐ Black

GLASS SIZE FORMULAS
Glass Size Formulas for Single Window Configurations 7200 Fixed Windows: • Glass Width = Frame Width Minus 2-1/4" (57.2) • Glass Height = Frame Height Minus 2-1/2" (63.5) 7200 Operable Windows: • Glass Width = Frame Width Minus 4-3/4" (120.7) • Glass Height = Frame Height Minus 5" (127) Glass Size Formulas for Multiple Window Configurations • Glass Width for All Multi-Lite Units = D.L.O. Plus 1" (25) • Glass Height for All Multi-Lite Units = D.L.O. Plus 1" (25) This formula can be used for all glass openings. • When utilizing subsills, subtract 1/2" (12.7) for CC281 or subtract 1" (25) for CC271 to the calculated glass height sizes.

OPTIONAL HARDWARE
☐ 90 Degree Egress 4-Bar Hinge (Verify Local Code) ☐ Butt Hinges (N/A PO & PI) (TV206, TV226 only) • Butt Hinges without Roto Operator Requires Friction Hold Open Hardware and Finger Pull B/O ☐ WH300 - Single Arm Roto Operator (TV206 only) • Roto Operators Require Butt Hinges ☐ WH412 - Lift Lever Handle (TV201, TV206 only) ☐ WH243 - Pole Operated Handle ☐ WH023 - Custodial Lock with Tamper Resistant Key Lock ☐ Screen with Fiber Mesh Gray ☐ Screen with Fiber Mesh Black ☐ Limit Stop ☐ Friction Adjustor ☐ WH063 - Pivot Shoe Roto Operator (TV201 only) ☐ WH248 - Finger Pull

FRAME OPTIONS	LENGTH
☐ CT268 - Curtain Wall Adaptor	24'2"
☐ CT210 - Nail Fin Adaptor	24'2"
☐ Prep and Install	☐ Stock Length

APPROVED BY _____ **DATE** _____

NOTE: PLEASE DOWNLOAD FORM TO SUBMIT. DO NOT FILL FORM ONLINE.

Email completed form to us_alum@usalum.com.
 Fax checklist to U.S. Aluminum Technical Sales at (877) 883-7547
 To review call (800) 627-6440. This form is available online at usalum.com.

FOR OFFICE USE ONLY
TAKEN BY: _____ PRICED BY: _____ EDITED BY: _____

MARK	QTY	DIM A (WIDTH)	DIM B (HEIGHT)	CASEMENT ONLY
				☐ HLSO ☐ HRSO
				☐ HLSO ☐ HRSO
				☐ HLSO ☐ HRSO
				☐ HLSO ☐ HRSO
				☐ HLSO ☐ HRSO
				☐ HLSO ☐ HRSO
				☐ HLSO ☐ HRSO
				☐ HLSO ☐ HRSO
				☐ HLSO ☐ HRSO

ADDITIONAL NOTES OR SKETCHES

APPROVED BY _____ DATE _____

FOR OFFICE USE ONLY

TAKEN BY: _____

PRICED BY: _____

EDITED BY: _____

WINDOWS SCHEMATICS: COMBINATION WINDOWS
Other configurations available per request. Please provide drawing.

PROJECT OUT BOTTOM VENT	PROJECT IN TOP VENT	FIXED	CASEMENT SWING OUT
			
			
 	 	 	 