

**NFRC 102-2010 THERMAL PERFORMANCE
TEST REPORT**

Rendered to:

CR LAURENCE CO., INC.

SERIES/MODEL: 8200 Horizontal Slider

TYPE: Horizontal Slider (Single)

Summary of Results

Standardized Thermal Transmittance (U-Factor)		0.47
Unit Size:		59" x 47-1/4" (1499 mm x 1200 mm) (Model Size)
Layer 1:	1/4"	Clear
Gap 1:	0.50"	A1-D: Aluminum Spacer
Layer 2:	1/4"	PPG Solarban 70XL (e=0.018*, #3)

Reference must be made to Report No. E0619.01-116-46, dated 01/16/15 for complete test specimen description and data.

NFRC 102-2010 THERMAL PERFORMANCE TEST REPORT

Rendered to:

CR LAURENCE CO., INC.
2100 East 38th Street
Vernon, California 90058

Report Number: E0619.01-116-46
Test Date: 12/18/14
Report Date: 01/16/15

Test Sample Identification:

Series/Model: 8200 Horizontal Slider

Type: Horizontal Slider (Single)

Overall Size: 59" x 47-1/4" (1499 mm x 1200 mm) (Model Size)

NFRC Standard Size: 59.1" x 47.2" (1500 mm wide x 1200 mm high)

Test Sample Submitted by: Client

Test Sample Submitted for: Validation for Initial Certification (Production Line Unit) & Plant Qualification

Test Procedure: U-factor tests were performed in a Guarded Hot Box in accordance with NFRC 102-2010, *Procedure for Measuring the Steady-State Thermal Transmittance of Fenestration Systems*.

Test Results Summary:

Standardized U-factor (U_{st}): 0.47 Btu/hr·ft²·F (CTS Method)

Test Sample Description:
Frame:

Material:	AT (0.25"): Aluminum with Thermal Breaks - All Members*		
Size:	59" x 47-1/4" (Model Size)		
Daylight Opening:	25-1/2" x 38-3/8"	Glazing Method:	Exterior
Exterior Color:	Clear	Exterior Finish:	Anodized
Interior Color:	Clear	Interior Finish:	Anodized
Corner Joinery:	Coped / Screws / Sealed		

*Fixed meeting stile was AT (0.25"). Head, sill and jambs were AT (0.31")

Active Sash:

Material:	AT (0.25"): Aluminum with Thermal Breaks - All Members		
Size:	30-1/4" x 42-3/4"		
Daylight Opening:	25-1/2" x 38-3/8"	Glazing Method:	Exterior
Exterior Color:	Clear	Exterior Finish:	Anodized
Interior Color:	Clear	Interior Finish:	Anodized
Corner Joinery:	Coped / Screws / Sealed		

Glazing Information:

Layer 1:	1/4"	Clear	
Gap 1:	0.50"	A1-D: Aluminum Spacer	100% Air*
Layer 2:	1/4"	PPG Solarban 70XL (e=0.018*, #3)	
Gas Fill Method:	N/A*		

*Stated per Client/Manufacturer

N/A Non-Applicable

Test Sample Description: (Continued)**Weatherstripping:**

Description	Quantity	Location
EPDM wedge gasket	1 row	Exterior glazing perimeter
Compression gasket	1 row	Interior glazing perimeter
Polypile with center fin	1 row	Head, sill, active jamb, fixed and active meeting stile
Vinyl glide strip	1 row	Head, sill, active jamb

Hardware:

Description	Quantity	Location
Spring-loaded latch	1	Active meeting stile
Metal keeper	1	Fixed meeting stile
Roller assembly	1 set	Bottom corners of active sash
Metal glide track	1	Active sash track sill
Aluminum insert	1	Fixed sash track sill
Aluminum insert	1	Active sash track at fixed jamb
Aluminum insert	1	Fixed sash track at active jamb

Drainage:

Drainage Method	Size	Quantity	Location
Weepslot with cover	1.50" x 0.25"	2	Sill face

Thermal Transmittance (U-factor)

Measured Test Data

Heat Flows

1. Total Measured Input into Metering Box (Q_{total})	805.48 Btu/hr
2. Surround Panel Heat Flow (Q_{sp})	100.71 Btu/hr
3. Surround Panel Thickness	4.00 inches
4. Surround Panel Conductance	0.0461 Btu/hr·ft ² ·F
5. Metering Box Wall Heat Flow (Q_{mb})	40.38 Btu/hr
6. EMF vs Heat Flow Equation (equivalent information)	0.0373*EMF + 0.300
7. Flanking Loss Heat Flow (Q_{fl})	13.42 Btu/hr
8. Net Specimen Heat Loss (Q_s)	650.97 Btu/hr

Areas

1. Test Specimen Projected Area (A_s)	19.36 ft ²
2. Test Specimen Interior Total (3-D) Surface Area (A_h)	22.23 ft ²
3. Test Specimen Exterior Total (3-D) Surface Area (A_c)	23.01 ft ²
4. Metering Box Opening Area (A_{mb})	52.94 ft ²
5. Metering Box Baffle Area (A_{bl})	46.97 ft ²
6. Surround Panel Interior Exposed Area (A_{sp})	33.58 ft ²

Test Conditions

1. Average Metering Room Air Temperature (t_h)	69.80 F
2. Average Cold Side Air Temperature (t_c)	-0.41 F
3. Average Guard/Environmental Air Temperature	71.25 F
4. Metering Room Average Relative Humidity	6.42 %
5. Metering Room Maximum Relative Humidity	6.91 %
6. Metering Room Minimum Relative Humidity	5.91 %
7. Measured Cold Side Wind Velocity (Perpendicular Flow)	12.66 mph
8. Measured Warm Side Wind Velocity (Parallel Flow)	NA mph
9. Measured Static Pressure Difference Across Test Specimen	0.00" ± 0.04" H ₂ O

Average Surface Temperatures

1. Metering Room Surround Panel	65.54 F
2. Cold Side Surround Panel	0.52 F

Results

1. Thermal Transmittance of Test Specimen (U_s)	0.48 Btu/hr·ft ² ·F
2. Standardized Thermal Transmittance of Test Specimen (U_{st})	0.47 Btu/hr·ft ² ·F

Thermal Transmittance (U-factor)

Calculated Test Data

CTS Method

1. Warm Side Emittance of Glass (e_1)	0.84
2. Cold Side Emittance of Glass	0.84
3. Warm Side Frame Emittance*	0.80
4. Cold Side Frame Emittance*	0.80
5. Warm Side Sash/Panel/Vent Emittance*	0.80
6. Cold Side Sash/Panel/Vent Emittance*	0.80
7. Warm Side Baffle Emittance (e_{b1})	0.92
8. Cold Side Baffle Emittance (e_{b2})	N/A
9. Equivalent Warm Side Surface Temperature	44.75 F
10. Equivalent Cold Side Surface Temperature	6.15 F
11. Warm Side Baffle Surface Temperature	69.49 F
12. Cold Side Baffle Surface Temperature	N/A F
13. Measured Warm Side Surface Conductance (h_h)	1.34 Btu/hr·ft ² ·F
14. Measured Cold Side Surface Conductance (h_c)	5.13 Btu/hr·ft ² ·F
15. Test Specimen Thermal Conductance (C_s)	0.87 Btu/hr·ft ² ·F
16. Convection Coefficient (K_c)	0.28 Btu/(hr·ft ² ·F ^{1.25})
17. Radiative Test Specimen Heat Flow (Q_{rl})	354.55 Btu/hr
18. Conductive Test Specimen Heat Flow (Q_{cl})	296.42 Btu/hr
19. Radiative Heat Flux of Test Specimen (q_{rl})	18.31 Btu/hr·ft ² ·F
20. Convective Heat Flux of Test Specimen (q_{cl})	15.31 Btu/hr·ft ² ·F
21. Standardized Warm Side Surface Conductance (h_{sth})	1.27 Btu/hr·ft ² ·F
22. Standardized Cold Side Surface Conductance (h_{stc})	5.28 Btu/hr·ft ² ·F
23. Standardized Thermal Transmittance (U_{st})	0.47 Btu/hr·ft ² ·F

Test Duration

1. The environmental systems were started at 17:22 hours, 12/17/14.
2. The test parameters were considered stable for two consecutive four hour test periods from 22:02 hours, 12/17/14 to 06:02 hours, 12/18/14.
3. The thermal performance test results were derived from 02:02 hours, 12/18/14 to 06:02 hours, 12/18/14.

The reported Standardized Thermal Transmittance (U_{st}) was determined using CTS Method, per Section 8.2(A) of NFRC 102.

*Stated per NFRC 101

Glazing Deflection:

	Frame	Active Sash
Edge Gap Width	0.50"	0.50"
Estimated center gap width upon receipt of specimen in laboratory (after stabilization)	0.50"	0.50"
Center gap width at laboratory ambient conditions on day of testing	0.50"	0.50"
Center gap width at test conditions	0.41"	0.41"

Glass collapse determined using a digital glass and air space meter

The sample was inspected for the formation of frost or condensation, which may influence the surface temperature measurements. The sample showed no evidence of condensation/frost at the conclusion of the test.

“This test method does not include procedures to determine the heat flow due to either air movement through the specimen or solar radiation effects. As a consequence, the thermal transmittance results obtained do not reflect performances which are expected from field installations due to not accounting for solar radiation, air leakage effects, and the thermal bridge effects that have the potential to occur due to the specific design and construction of the fenestration system opening. The latter can only be determined by in-situ measurements. Therefore, it is important to recognize that the thermal transmittance results obtained from this test method are for ideal laboratory conditions and should only be used for fenestration product comparisons and as input to thermal performance analyses which also include solar, air leakage and thermal bridge effects.”

The test sample was installed in a vertical orientation, the exterior of the specimen was exposed to the cold side. The direction of heat transfer was from the interior (warm side) to the exterior (cold side) of the specimen. The ratings were rounded in accordance to NFRC 601, NFRC Unit and Measurement Policy. The data acquisition frequency is 5 minutes.

ANSI/NCSL Z540-2-1997 type B uncertainty for this test was 2.31%.

Required annual calibrations for the Architectural Testing Inc. 'thermal test chamber' (ICN 000001) in York, Pennsylvania were last conducted in May 2014 in accordance with Architectural Testing Inc. calibration procedure. A CTS Calibration verification was performed May 2014. A Metering Box Wall Transducer and Surround Panel Flanking Loss Characterization was performed September 2014.

"Ratings included in this report are for submittal to an NFRC licensed IA for certification purposes and are not meant to be used for labeling purposes. Only those values identified on a valid Certification Authorization Report (CAR) are to be used for labeling purposes."

Architectural Testing, Inc. will service this report for the entire test record retention period. Test records that are retained such as detailed drawings, datasheets, representative samples of test specimens, or other pertinent project documentation will be retained by Architectural Testing, Inc. for the entire test record retention period. The test record retention end date for this report is December 18, 2018.

This report does not constitute certification of this product nor an opinion or endorsement by this laboratory. It is the exclusive property of the client so named herein and relates only to the specimen tested. This report may not be reproduced, except in full, without the written approval of Architectural Testing, Inc.

For ARCHITECTURAL TESTING, INC.

Tested By:

Ryan P. Moser
Technician

Reviewed By:

Shon W. Einsig
Senior Technician
Individual-In-Responsible-Charge

RPM:klb
E0619.01-116-46

Attachments (pages): This report is complete only when all attachments listed are included.

- Appendix-A: CTS Calibration Data (1)
- Appendix-B: Surround Panel Wiring Diagram (1)
- Appendix-C: Baffle Wiring Diagram (1)
- Appendix-D: Submittal Form and Drawings (20)

 ACCREDITED	Architectural Testing, Inc. is accredited by the International Accreditation Service (IAS) under the specific test methods listed under lab code TL-144, in accordance with the recognized International Standard ISO/IEC 17025:2005. The laboratory's accreditation or test report in no way constitutes or implies product certification, approval, or endorsement by IAS.
---	--

Revision Log

<u>Rev. #</u>	<u>Date</u>	<u>Page(s)</u>	<u>Revision(s)</u>
.01R0	01/16/15	All	Original Report Issue. Work requested by Gyu-Hyeon Kim of CR Laurence Co., Inc.

Appendix A: CTS Calibration Data

1. CTS Test Date	12/03/13
2. CTS Size	19.38 ft ²
3. CTS Glass/Core Conductance	0.42 Btu/hr·ft ² ·F
4. Warm Side Air Temperature	69.80 F
5. Cold Side Air Temperature	-0.40 F
6. Warm Side Average Surface Temperature	53.63 F
7. Cold Side Average Surface Temperature	3.69 F
8. Convection Coefficient (K _c)	0.28 Btu/(hr·ft ² ·F ^{1.25})
9. Measured Cold Side Surface Conductance (h _c)	5.13 Btu/hr·ft ² ·F
10. Measured Thermal Transmittance	0.30 Btu/hr·ft ² ·F

Appendix B: Surround Panel Wiring Diagram

+1

+2

+3


+4

+5

+6

+7

+8



Appendix C: Baffle Wiring Diagram

Appendix D: Submittal Form and Drawings

NFRC PRODUCT CERTIFICATION PROGRAM

Submittal Form for Test Samples

For use by manufacturers, lineal suppliers and fabricators



1. Information on Production of the Test Sample (complete ALL fields):

Manufacturer: CRL - US Aluminum Date of sample manufacture: 11/7/2014

Plant Address where manufactured: 2100 E 38th St

City: Los Angeles State: CA Zip Code: 90085-1617

Name of IA: Associated Laboratories, Inc Phone: (214)565-0593 Fax: (214)565-1094

2. Product Information (complete ALL fields):

Product Line ID (CPD) No.: 5559 Product/Operator Type
(Table 4-3 of NFRC 100): Horizontal Slider

Series/Model: 8200 Horizontal Slider

3. Test sample is being submitted for (select ONE):

- a. Validation for Initial Certification (prototype only) no plant qualification
- b. Validation for Initial Certification (production line unit) & plant qualification
- c. Validation for Recertification (production line unit) & plant qualification
- d. Plant Qualification Only (production line unit)

I, Gyu Hyeon Kim, as the designated agent for CRL - US Aluminum

do hereby attest that the foregoing information is true to the best of my information, knowledge, and belief. Further, if the unit is identified in Section 3 as a production line unit, I hereby authorize the NFRC-accredited testing laboratory to send a copy of the test report to the IA identified above for plant qualification purposes pursuant to the NFRC Product Certification Program..

Signature: Gyu Hyeon Kim Digitally signed by Gyu Hyeon Kim
Date: 2015.01.15 14:39:58 -08'00' Date: 1/15/2015

FOR LABORATORY USE ONLY

1. Laboratory

2. Date Sample Received: 11/11/14 File number ID: E0619

3. Date Sample Tested: 12/18/14 By: RPM


4. Modifications made: _____

5. Reason for non-testing of sample unit: _____


[Note: If the sample submitted can not be tested due to damage prior to testing, a new sample and new form shall be submitted to the testing laboratory. Both forms shall be submitted to the IA when the testing is completed.]

8200 SERIES HORIZONTAL SLIDING WINDOW SYSTEM


HEADS




8200 HEAD
HORIZONTAL SLIDING
- FIN - FIXED
HS801 / SH865 / HS811



8200 HEAD
HORIZONTAL SLIDING
- FIN - OPERABLE
HS801 / SH865 / HS811




8200 HEAD
HORIZONTAL SLIDING
- BLOCK - FIXED
HS862 / SH865 / HS811




8200 HEAD
HORIZONTAL SLIDING
- BLOCK - OPERABLE
HS862 / SH865 / HS811


SILLS




8200 SILL
HORIZONTAL SLIDING
- FIN - FIXED
SH865 / HS804 / HS813 / HS803



8200 SILL
HORIZONTAL SLIDING
- FIN - OPERABLE
HS838 / SH865 / HS813 / HS803 / HS804




8200 SILL
HORIZONTAL SLIDING
- BLOCK - FIXED
SH865 / HS813 / HS804 / HS863




8200 SILL
HORIZONTAL SLIDING
- BLOCK - OPERABLE
HS838 / HS804 / HS813 / HS863 / HS865


JAMBS




8200 JAMB
HORIZONTAL SLIDING
- FIN - OPERABLE
HS815 / HS805 / HS836 / SH865



8200 JAMB
HORIZONTAL SLIDING
- FIN - FIXED
HS805 / PW803




8200 JAMB
HORIZONTAL SLIDING
- BLOCK - OPERABLE
HS864 / HS836 / SH865



8200 JAMB
HORIZONTAL SLIDING
- BLOCK - FIXED
HS864 / PW803 / SH865

INTERLOCK







8200 INTERLOCK
HORIZONTAL SLIDING
HS854 / SH865 / HS866

	Report #: E0619-116-46
Date:	12/18/2014
Verified by:	Ryan P. Moser



Report #: E0619-116-46
 Date: 12/18/2014
 Verified by: Ryan P. Moser



U.S. ALUMINUM CORP.

H-61616

8200HS HEAD
HS801

TER MEER
FULL SIZE


05/19/10

NOTES:

1. 6063-T5 ALLOY AND TEMPER.
2. ASSEMBLES WITH SH865; DIE# 61595
3. PAINT PERIMETER: 3. 610"
4. DEBRIDGE WITH A .375 X .015 MAX PENETRATION INTO THERMAL AREA.
5. THERMAL DETAIL AREA: .203
6. OUTSIDE PERIMETER: 30. 48
7. Y INDICATES POSSIBLE STREAKS

Debridged 0.31"


DENTS ARE POSSIBLE ON THIS LEG



	1. 479	C-1817	1
	1. 775	4. 958	PORTHOLE 12X6. 5
	36. 690	HOLLOW II	15x8. 5 61616
21	8" 36/PRESS 4		H-61616
			.085



Report #: E0619-116-46
 Date: 12/18/2014
 Verified by: Ryan P. Moser





Report #: E0619-116-46

Date: 12/18/2014

Architectural Testing Verified by: Ryan P. Maser

U.S. ALUMINUM CORP.

T-61618





8200HS SILL INSERT

TER MEER


05/26/10

HS804

FULL SIZE

**NOTES:**

1. 6063-T5 ALLOY AND TEMPER.
2. ASSEMBLES WITH HS803; DIE# 61617
3. PAINT PERIMETER: 2. 444"
4. DEBRIDGE WITH A .375 x .015 MAX PENETRATION INTO THERMAL AREA.
5. THERMAL DETAIL AREA: .328, "EE"



	1. 507	C-1819	1
	1. 808	4. 804	10 X 61618
	27. 761	SOLID	15X8.5 61618
	15	8" 35/PRESS 4	T-61618

.118



Report #: E0619-116-46
Date: 12/18/2014
Verified by: Bryan P. Moser

U.S. ALUMINUM CORP.

T-61619

05/18/10

Technical drawing of a mechanical assembly with various dimensions and part numbers. The drawing includes a large central vertical pipe with horizontal sections, various fittings, and a bottom section with a circular component. Dimensions are labeled in millimeters (e.g., 335, 154, 040, 135 PT, 045, 025 R., 996, 1353, 045, 031 R., 222, 035 R., 231 PT, 352, 106, 062, 093 R., 062, 100, 066, 020 R., 490, 080, 062, 100, 0335, 0100, 0154, 0040, 0135 PT, 0045, 0025 R., 0996, 1353, 0045, 0031 R., 0222, 0035 R., 0231 PT). Labels include 'FULL R.' and '(2)' near the top right, and 'DETAIL' at the bottom right.

Technical drawing of Detail B, showing a cross-section of a mechanical part. The drawing includes the following dimensions:

- Width: .857
- Thickness: .031 R. (5)
- Bottom width: .165
- Bottom thickness: .062
- Bottom gap: .062
- Bottom height: .282 .406
- Bottom radius: .050
- Left side thickness: .020 R. (8)
- Left side gap: .040
- Left side height: .116
- Bottom hole diameter: 375
- Bottom hole width: .687
- Top gap: .025 R. (2)
- Top width: .062
- Top thickness: .062
- Top height: .282 .406
- Top radius: .050
- Bottom right corner radius: .250
- Bottom right corner height: 1.250

Detail "B" is located at the bottom center of the drawing, with a size of 2 X 1/2".

DETAIL "E"

SHARP

010 R.

15°

PTA

.445

.097

.180

.040

.020

.062 R.

.040

.056

.074

170

4 X SIZE

DETAIL "C"

NOTES:

1. 6063-T5 ALLOY AND TEMPER.
2. ASSEMBLES WITH SH865; DIE# 61595
3. PAINT PERIMETER: 3.828"
4. DEBRIDGE WITH A .375 X .015 MAX PENETRATION INTO THERMAL AREA.
5. THERMAL DETAIL AREA: .209, "EE"
6.  INDICATES POSSIBLE STREAKS


This technical drawing shows a cross-sectional view of a mechanical assembly. The drawing is labeled with several dimensions and features:

- Dimensions:**
 - Left side: .250, 1.250, .821, .352, .072, .045 R., .110, .200, 1.853, 4.500.
 - Top center: 1.375, .062, .010, .200, .225, .772, 1.808, 1.308, .062 (3), .469, .437, 2.009.
 - Bottom center: .031 R. (21), .231, .050 +.045 -.010, 2.246, 170, .062 R., .445.
 - Right side: REF. 882, .188, .445.
- Annotations:**
 - "SHARP (10)" is indicated near a sharp corner.
 - "DENTS ARE POSSIBLE ON THE LEG" is written near a vertical leg.
 - "EXPOSED" is written vertically on the left and right sides.
 - "PT" is written near several dimension lines.
 - "REF." is written near the bottom center.
 - "A" and "C" are circled with yellow markers.
 - Red lines and arrows highlight specific features: a red line with a red arrow points to the top center area; a red line with a red arrow points to the right side; a red line with a red arrow points to the bottom center area; and a red line with a red arrow points to the bottom right area.
 - Green checkmarks are placed on the left side, right side, and bottom right side.



<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	9 X 2 DIE 172 RECESS
			085
	1. 044	C-1822	1
	1. 253	4. 909	9 X 61619
	27. 169	SOLID	61607
	22	8" 51/PRESS 4	T-61619



Report #: E0619-116-46
 Date: 12/18/2014
 Verified by: Ryan P. Moyer




DETAIL "A"
4 X SIZE



DETAIL "B"
4 X SIZE

			U.S. ALUMINUM CORP.	T-61620
	8000HS TOP RAIL	TER MEER	04/18/10	
	HS811	2 X SIZE		



NOTES:

1. 6063-T5 ALLOY AND TEMPER.
2. MATES WITH SH865; DIE# 61595
3. DEBRIDGE WITH A .312 X .015 MAX PENETRATION INTO THERMAL AREA.
4. THERMAL DETAIL AREA: .147; (MODIFIED "DD")
5. PAINT PERIMETER: 5.240"
6. ▶ INDICATES POSSIBLE STREAKS

Debrided 0.25"

9X2 DIE 1/2 RECESS

				.084
	.450	C-1820	2	
	.540	2.611	9 X 61620	
	11.331	SOLID	2-1	
	21	7" 45/PRESS 3	T-61620	



Report #: E0619-116-46

Date: 12/18/2014

Verified by: Ryan P. Moser

U.S. ALUMINUM CORP.

T-6162

04/18/10


8000HS BOTTOM RAIL

TER MEER

04/18/10


NOTES :

- 6063-T5 ALLOY AND TEMPER.
- MATES WITH SH865; DIE# 61595
- DEBRIDGE WITH A .250 x .015 MAX PENETRATION INTO THERMAL AREA.
- THERMAL DETAIL AREA: .116;
(MODIFIED "CC")
- PAINT PERIMETER: 11.270"
- INDICATES POSSIBLE STREAKS




DETAIL "A"

4 X SIZE




ACTUAL SIZE



DETAIL "B"

4 X SIZE



9X2 DIE 1/2 RECESS

. 084

1


9 X 61621

· 32121


□	673	C-1821	1
□	808	3, 306	9 X 61621
	16, 937	SOLID	32121
	21	7" 61/PRESS 3	I-61621



Report #: E0619-116-46
 Date: 12/18/2014
 Verified by: *Ryan P. Moser*




ACTUAL SIZE



NOTES:

1. 6063-T6 ALLOY AND TEMPER.
2. MATES WITH SH865; DIE# 61595
3. DEBRIDGE WITH A .312 x .015 MAX PENETRATION INTO THERMAL AREA.
4. THERMAL DETAIL AREA: .228; (MODIFIED "DD")
5. PAINT PERIMETER: 9.732"
6. OUTSIDE PERIMETER: 14.338
7. INDICATES POSSIBLE STREAKS

			U.S. ALUMINUM CORP.	H-61632
		8200HS SERIES VENT STILE	TER MEER	04/17/10
	HS815		2 X SIZE	




<input type="checkbox"/>	<input type="checkbox"/>	.084		
		.780	C-1823	1
		.936	3.482	PORTHOLE 10X5.5
		19.701	HOLLOW III	61588
		21	8" 68/PRESS 4	H-61632



Report #: E0619-116-46

Date: 12/18/2014

Verified by: Ryan P. Moser



NOTES.

1. 6063-T6 ALLOY AND TEMPER.
2. MATES WITH SH865; DIE 61595
3. DEBRIDGE WITH A .312 X .015 MAX PENETRATION INTO THERMAL AREA.
4. THERMAL DETAIL AREA: .208;
(MODIFIED "DD")
5. PAINT PERIMETER: 6. 418"
- ⑥ 6. OUTSIDE PERIMETER: 18. 969
7. ▷INDICATES POSSIBLE STREAKS

SECTION PROPERTIES



$$I_{xx} = 0.552 \text{ in}^4$$

$$S_{xx} = 0.294 \text{ in}^3$$

$$I_{yy} = 0.669 \text{ in}^4$$

$$S_{xx} = 0.553 \text{ in}^3$$

N PROPERTIES		MAX SIZE	
<input type="checkbox"/>	<input type="checkbox"/>		.062
<input type="checkbox"/>		1. 148 (B)	C-1787
		1. 378 (B)	3. 447
		25. 465 (B)	HOLLOW II
		18 (B)	8" 47/PRESS 4
			H-6159






Report #: E0619-116-46

Date: 12/18/2014

Verified by: Ryan P. Moser

NOTES :

1. 6063-T5 ALLOY AND TEMPER.
2. SNAP FITS WITH HS804; DIE #61618
3. PAINT PERIMETER: 2. 578"



U.S. ALUMINUM CORP.

T-61634

SCREEN FRAME

TER MEE


08/13/10

AT SILL


TER MEE

08/13/10

ACTUAL SIZE



DETAIL "A"



9X2 DIE 1/2 RECESS

.050


151	C-1855	4
181	1. 845	9 X 61634
5. 964	SOLID	42772
33	7" 68/PRESS 3	T-61634



Report #: E0619-116-46

Date: 12/18/2014

Verified by: Ryan P. Moser




				U.S. ALUMINUM CORP.	T-61635	
				SCREEN FRAME AT JAMB	TER MEER	08/13/10
				HS836	4 X SIZE	

NOTES:

1. 6063-T5 ALLOY AND TEMPER.
2. SNAP FITS WITH HS805; DIE #61619
HS864; DIE #61626
3. PAINT PERIMETER: 2. 358"



ACTUAL SIZE



DETAIL "A"

8 X SIZE

9X2 DIE 1/2 RECESS




Report #: E0619-116-46

Date: 12/18/2014

Architectural Testing Verified by:

Ryan P. Moser

8000SH-011



OTES:

1. AREA: .308 IN²
2. MATERIAL: EPDM SPONGE
3. PART NO. NP881

					UNITED STATES ALUMINUM CORP.	
				Willie C.	INTERIOR GLAZING GASKET (8000 SH WINDOW)	
				02/05/10	PART# NP881	8000SH-011
				4 X SIZE		



Report #: E0619-116-46


Date: 12/18/2014

—
Architectural Testing

Architectural Testing Verified by: Ryan P. Moser

8000SH-038B

REF. DRAWING: IW1841



ACTUAL SIZE

RADIUS SCHEDULE

s	-	SHARP
a	-	. 006 R.
b	-	. 012 R.
u	-	. 015 R.
d	-	. 020 R.
e	-	. 030 R.
f	-	. 045 R.
g	-	. 060 R.

NOTES :

1. MATERIAL: RIGID PVC TO MEET AAMA 303-07
2. ALL UNSPECIFIED RADII = .020
3. TYPICAL EXTERIOR WALL THICKNESS: .050
TYPICAL INTERIOR WALL THICKNESS: .025
4. AREA: .181
5. MINIMUM SHEEN ALLOWED 56.0 USING A
GARDNER MICRO-GLOSS 60° GLOSS METER.
6. TOLERANCE UNLESS OTHERWISE NOTED \pm .012
7. WALL THICKNESS TOLERANCE TO BE: \pm .006

IWC TOLERANCES FOR PVC EXTRUDED SHAPES APPLY UNLESS SPECIFICALLY SHOWN OTHERWISE

INTERNATIONAL WINDOW CORP.

RELEASE FOR PRODUCTION
DATE: MARCH 9, 2010
APPRV'D BY JOHN FREY




Report #: E0619-116-46

Date: 12/18/2014

Architectural Testing Verified by: Ryan P. Moser

8200HS-051



RADIUS SCHEDULE

s	-	SHARP
o	-	.006 R.
b	-	.012 R.
u	-	.015 R.
d	-	.020 R.
e	-	.030 R.
f	-	.045 R.
g	-	.060 R.



ACTUAL SIZE

NOTES:

1. MATERIAL: RIGID PVC TO MEET AAMA 303-07
2. ALL UNSPECIFIED RADII = .012
3. TYPICAL EXTERIOR WALL THICKNESS: .050
TYPICAL INTERIOR WALL THICKNESS: .020
4. AREA: .317
5. MINIMUM SHEEN ALLOWED 56.0 USING A
GARDNER MICRO-GLOSS 60° GLOSS METER.
6. TOLERANCE UNLESS OTHERWISE NOTED \pm .012
7. WALL THICKNESS TOLERANCE TO BE: \pm .006


© 2009 COPYRIGHT, ALL RIGHTS RESERVED

IWC TOLERANCES FOR PVC EXTRUDED SHAPES APPLY UNLESS SPECIFICALLY SHOWN OTHERWISE


INTERNATIONAL WINDOW CORP.

TER MEER HEAD ISOLATOR
05/14/10 PART NO: WH838
4 X SIZE SERIES: 8200HS

8200HS-051




FULL SIZE



NOTES:

1. MATERIAL . 032 STAINLESS STEEL
2. AS SUPPLIED BY:
STEVE HAAG & ASSOC. OR EQUAL
3. VPN: SS71-HD-SS-032-24



2100 E. 38TH STREET VERNON, CA 90058
PHONE: (323) 588-128 FAX: (323) 232-2523

DIVISION

UNITED STATES ALUMINUM

DRWN BY:

1

SCALE:

SS TRACK
PART# WH22342.0024
8200 HORIZONTAL
SLIDER

DWG NO.



Report #: E0619-116-46


Date: 12/18/2014

Verified by: Ryan P. Moser

USA-2957



ACTUAL SIZE



NOTES:

1. AREA = .151 in²
2. MATERIAL: EPDM DENSE
3. DUROMETER: 70 ±5 SHORE
4. PART NO. NP825

U.S. ALUMINUM CORP.

PRESTON

05/16/06

4 X SIZE

EXTERIOR GLAZING GASKET FOR TG500/TG600 SYSTEM

PART# : NP825

USA-2957




Report #: E0619-116-46
Date: 12/18/2014
Architectural Testing Verified by: *Ryan P. Moser*

USA-3180



ACTUAL SIZE



NOTES:

1. MATERIAL: POLYPROPYLENE
2. COLOR: BLACK
3. RYKO NO: R-11125

INTERNATIONAL WINDOW CORP.

BRIAN R.

09/06/12


4 X SIZE

VENT GUIDE STRIP

PART NO: NP942

USA-3180

G2 FLATBACK TRIPLE FIN



Ref	Description	Dimension	Tolerance
A	Pile Height	.250	+.010 -.005
B	Center Fin Height	.280	+.010 -.010
C	Backing Width	.270	+.005 -.005
D	Backing Thickness	.030	+.003 -.003



THIS DOCUMENT DISCLOSES INFORMATION AND DATA TO WHICH AMESBURY GROUP INC. HAS PROPRIETARY RIGHTS. NEITHER RECEIPT NOR POSSESSION THEREOF CONFERs OR TRANSFERS ANY RIGHT TO REPRODUCE, USE OR DISCLOSE IN WHOLE OR IN PART ANY SUCH INFORMATION AND DATA EXCEPT BY WRITTEN PERMISSION FROM AMESBURY GROUP INC.

JH1102

REV	DATE	MODIFICATION	TITLE: G2 FLATBACK TRIPLE FIN		DIMENSIONS ARE IN INCHES UNLESS INDICATED OTHERWISE		MATERIAL: POLYPROPYLENE	PART NO. 25027045BKGBT	REV. B			
B	9/11/13	Added information for 2022M	DRAWN: GMS		TOLERANCES - UNLESS INDICATED OTHERWISE							
			Fractions ±1/64"		Decimals .X ±.020"							
			Angles ±0.5°		.XX ±.010"							
			XXX ±.005"									




Report #: E0619-116-46

Date: 12/18/2014

Architectural Testing Verified by:

Ryan P. Moser



DETAIL FOR THERMAL MODELING OF
ALUMINUM SPACER (A1-D)