


**Vertical Hole Spacing**

Non cumulative tolerances on hole to hole spacing.

	Metric (mm)	Decimal (in.)
A	2414.0 $\pm.000$	95.039 $\pm.000$
B	38.6 $\pm.025$	1.520 $\pm.010$
C	63.5 $\pm.020$	2.500 $\pm.008$
D	184.2 $\pm.020$	7.250 $\pm.008$
E	247.7 $\pm.020$	9.750 $\pm.008$
F	260.4 $\pm.020$	10.250 $\pm.008$
G	304.8 $\pm.020$	12.000 $\pm.008$
M	171.5 $\pm.020$	6.750 $\pm.008$
N	263.5 $\pm.020$	10.375 $\pm.008$
O	387.4 $\pm.020$	15.250 $\pm.008$
P	346.1 $\pm.020$	13.625 $\pm.008$
R	76.7 $\pm.020$	3.020 $\pm.008$
S	209.6 $\pm.020$	8.250 $\pm.008$



1.020" [25.9mm] Ref.  
 End of hinge to first bearing, both ends.

**HAGER COMPANIES**  
 HIGHWAY 78 WEST  
 P.O. BOX 3368  
 OXFORD, ALABAMA 36203

780-210 95" SD

DATE 10-25-96	REV. 01-15-02	DR. KBJ	SCALE None
FILENAME z:\rton\template\standard\780-210.dwg			
DRAWING NO.		780210095SD	