

JR. GENEVA

Wall Mount Hinge – Short Back Plate

CAT. NO. JJRG074

***NOTE:** Do not exceed either maximum weight or width when choosing proper quantity of hinges.

Important Information:

- 1) The Jr. Geneva Series of Hinges are equipped with a dual degree pivot pin. The pivot pin is set by the manufacturer for normal door closing position. You have the option of altering the closing position of the door 5 degrees by utilizing the opposite side of the pivot pin, which has been pre-machined (see Section 3 for this procedure).
- 2) The clearance gap required at the hinge side is $1/32"$ to $5/32"$. For a clearance gap of $1/8"$ to $1/4"$, see template for Cat. No. JJRG037.

Specifications:

Glass Sizes: $1/4"$ (6mm) to $5/16"$ (8mm) thick tempered safety glass
Construction: Solid brass
Closing Type: Self-centering when within 15° of closed position
Cutout Required
Includes: Gaskets, screws and template

Maximum Door Capacities for Two Hinges or Three Hinges

Maximum Door Weight:	62 lbs. (28 kg)	92 lbs. (32 kg)
Maximum Door Width:	28" (711mm)	32" (813mm)

Use of Gaskets:

For $1/4"$ (6mm) Glass: Use one thick gasket on each side
For $5/16"$ (8mm) Glass: Use one thin gasket on each side

Recommendations:



For public safety, we recommend the use of only tempered safety glass. Do not use power tools when installing these hinges.

Maintenance Guidelines:

- Our hinges are greased at the factory for quiet and trouble-free operation. If there is any squeaking that occurs after installation, put a drop of "3 in 1 Oil" (also known as "household oil") on the white nylon washer that the hinge body pivots on. This washer is the component that acts as a buffer, so the body of the hinge doesn't pivot directly on the brass center block. This solution doesn't require the disassembly of the hinge. **Note: Do not use spray lubricant on these hinges.** If the hinge has been disassembled, upon re-assembly, use white lithium grease to lubricate the interior mechanism.
- Never use an abrasive cleaner on the hardware. Many of the components are coated with a clear lacquer that will be irreparably damaged if subjected to harsh, abrasive chemicals. Advise your customer that drying the hardware with a clean, soft towel on a daily basis is the best way to maintain the hardware. If mineral deposits build-up, mix a couple of drops of a mild liquid soap (such as Ivory or a similar product) into a cup of warm water. Using a soft, non-abrasive cloth, clean the hardware. Rinse thoroughly with clean, warm water and dry.



IMPORTANT: Project measurements from the edge of the glass.



ALWAYS USE DIMENSIONS
TO ENSURE ACCURACY

JR. GENEVA

Wall Mount Hinge – Short Back Plate

CAT. NO. JJRG074

For Technical Assistance in the United States and Canada 1.800.421.6144. Press 2, then option 1

C.R. Laurence Co., Inc. • 2503 E. Vernon Ave., Los Angeles, CA 90058 • 1.800.421.6144 • crlaurence.com