



# SAFETY DATA SHEET

crlaurence.com

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document Group:** 08-7522-9  
**Issue Date:** 08/23/18

**Version Number:** 12.04  
**Supersedes Date:** 08/22/18

## SECTION 1: Identification

### 1.1. Product identifier

3M™ Fast Cure Auto Glass Urethane, PN 08566, 08689, 08690

**CRL CATALOG NUMBER:** 3M8690

### Product Identification Numbers

ID Number	UPC	ID Number	UPC
60-9800-3228-2	00-51135-08690-2	60-9800-3558-2	00051135086896
60-9800-3918-8	00-51135-08566-0		

7000144585, 7000148240, 7010364098, 7000120469, 7000144586

### 1.2. Recommended use and restrictions on use

#### Recommended use

Automotive, Adhesive/Sealant for Windshields

### 1.3. Supplier's details

**MANUFACTURER:** 3M  
**DIVISION:** Automotive Aftermarket  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA  
**Telephone:** 1-888-3M HELPS (1-888-364-3577)

### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

## SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1.

Carcinogenicity: Category 2.

### 2.2. Label elements

**Signal word**

Danger

**Symbols**

Health Hazard |

**Pictograms****Hazard Statements**

Causes eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

**Precautionary Statements****Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray.

In case of inadequate ventilation wear respiratory protection.

Wear protective gloves.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

39% of the mixture consists of ingredients of unknown acute oral toxicity.

**SECTION 3: Composition/information on ingredients**

<b>Ingredient</b>	<b>C.A.S. No.</b>	<b>% by Wt</b>
Polyether (NJTS: 04499600-7082)	Trade Secret*	30 - 60 Trade Secret *
Carbon Black	1333-86-4	10 - 30 Trade Secret *
Phenol Alkyl Sulfonate (NJTS: 04499600-7083)	Trade Secret*	10 - 30 Trade Secret *

Kaolin, Calcined	92704-41-1	7 - 13 Trade Secret *
Hydrotreated Light Petroleum Distillates	64742-47-8	1 - 5 Trade Secret *
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	0.1 - 0.5 Trade Secret *
Dibutyltin Dichloride	683-18-1	< 0.08 Trade Secret *

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

DO NOT USE WATER

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode. None inherent in this product.

#### Hazardous Decomposition or By-Products

##### Substance

Carbon monoxide  
Carbon dioxide

##### Condition

During Combustion  
During Combustion

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

## 6.2. Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

For industrial or professional use only. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

## 7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from amines.

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	ACGIH	TWA:0.005 ppm	
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	OSHA	CEIL:0.2 mg/m <sup>3</sup> (0.02 ppm)	
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m <sup>3</sup>	A3: Confirmed animal carcin.
Carbon Black	1333-86-4	OSHA	TWA:3.5 mg/m <sup>3</sup>	
JET FUELS (NON-AEROSOL), AS TOTAL HYDROCARBON VAPOR	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m <sup>3</sup>	A3: Confirmed animal carcin., SKIN
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m <sup>3</sup>	A3: Confirmed animal carcin., SKIN
TIN, ORGANIC COMPOUNDS	683-18-1	ACGIH	TWA(as Sn):0.1 mg/m <sup>3</sup> ;STEL(as Sn):0.2 mg/m <sup>3</sup>	SKIN, A4: Not class. as human carcin
TIN, ORGANIC COMPOUNDS	683-18-1	OSHA	TWA(as Sn):0.1 mg/m <sup>3</sup>	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit  
CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile Rubber

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>General Physical Form:</b>	Solid
<b>Specific Physical Form:</b>	Paste
<b>Odor, Color, Grade:</b>	Slight odor Black paste
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>No Data Available</i>
<b>Boiling Point</b>	192 - 200 °C
<b>Flash Point</b>	No flash point
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Flammability (solid, gas)</b>	Not Classified
<b>Flammable Limits(LEL)</b>	<i>Not Applicable</i>
<b>Flammable Limits(UEL)</b>	<i>Not Applicable</i>
<b>Vapor Pressure</b>	<i>No Data Available</i>
<b>Vapor Density</b>	<i>No Data Available</i>
<b>Density</b>	1.215 g/ml
<b>Specific Gravity</b>	1.20 [Ref Std: WATER=1]
<b>Solubility in Water</b>	Negligible
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>

Autoignition temperature	> 200 °C
Decomposition temperature	No Data Available
Viscosity	No Data Available
Hazardous Air Pollutants	0.0033 lb HAPS/lb solids [ <i>Test Method</i> :Calculated]
Molecular weight	No Data Available
Volatile Organic Compounds	37 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]
Volatile Organic Compounds	3.1 % weight [ <i>Test Method</i> :calculated per CARB title 2]
Percent volatile	1.70 % weight [ <i>Details</i> :Excluding exempt compounds]
VOC Less H2O & Exempt Solvents	37 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization may occur. Reacts with water.

### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Amines

Alcohols

Water

### 10.6. Hazardous decomposition products

#### Substance

None known.

#### Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

#### Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

#### Additional Health Effects:

#### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

<b><u>Ingredient</u></b>	<b><u>CAS No.</u></b>	<b><u>Class Description</u></b>	<b><u>Regulation</u></b>
Carbon Black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

#### Additional Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

<b><u>Name</u></b>	<b><u>Route</u></b>	<b><u>Species</u></b>	<b><u>Value</u></b>
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Phenol Alkyl Sulfonate (NJTS: 04499600-7083)	Dermal	Rat	LD50 > 1,000 mg/kg
Phenol Alkyl Sulfonate (NJTS: 04499600-7083)	Ingestion	Rat	LD50 > 5,000 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg
Kaolin, Calcined	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Kaolin, Calcined	Ingestion	Rat	LD50 > 2,000 mg/kg
Hydrotreated Light Petroleum Distillates	Dermal	Rabbit	LD50 > 3,160 mg/kg
Hydrotreated Light Petroleum Distillates	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Hydrotreated Light Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
P,P'-Methylenebis(phenyl isocyanate)	Dermal	Rabbit	LD50 > 5,000 mg/kg
P,P'-Methylenebis(phenyl isocyanate)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
P,P'-Methylenebis(phenyl isocyanate)	Ingestion	Rat	LD50 31,600 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

<b><u>Name</u></b>	<b><u>Species</u></b>	<b><u>Value</u></b>
Carbon Black	Rabbit	No significant irritation
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant

P,P'-Methylenebis(phenyl isocyanate)	official classification	Irritant
--------------------------------------	-------------------------	----------

**Serious Eye Damage/Irritation**

Name	Species	Value
Carbon Black	Rabbit	No significant irritation
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
P,P'-Methylenebis(phenyl isocyanate)	official classification	Severe irritant

**Skin Sensitization**

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Guinea pig	Not classified
P,P'-Methylenebis(phenyl isocyanate)	official classification	Sensitizing

**Respiratory Sensitization**

Name	Species	Value
P,P'-Methylenebis(phenyl isocyanate)	Human	Sensitizing

**Germ Cell Mutagenicity**

Name	Route	Value
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification
Hydrotreated Light Petroleum Distillates	In Vitro	Not mutagenic
P,P'-Methylenebis(phenyl isocyanate)	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic
Hydrotreated Light Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Hydrotreated Light	Inhalation	central nervous	May cause drowsiness or	Human	NOAEL Not	



Petroleum Distillates		system depression	dizziness	and animal	available	
Hydrotreated Light Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Hydrotreated Light Petroleum Distillates	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks

**Aspiration Hazard**

Name	Value
Hydrotreated Light Petroleum Distillates	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information**

**15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:****Physical Hazards**

Not applicable

**Health Hazards**

Carcinogenicity

Serious eye damage or eye irritation

**15.2. State Regulations**

Contact 3M for more information.

**California Proposition 65****Ingredient**

Carbon Black

**C.A.S. No.**

1333-86-4

**Listing**

Carcinogen

**15.3. Chemical Inventories**

The components of this product are in compliance with the chemical notification requirements of TSCA. One or more chemical components of this material have been commercialized under the TSCA polymer exemption at 40CFR723.250. Polymers subject to this exemption are not listed on the TSCA Inventory, but are in compliance with TSCA requirements.

Contact 3M for more information.

**15.4. International Regulations**

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

**SECTION 16: Other information****NFPA Hazard Classification**

**Health:** 2 **Flammability:** 2 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Document Group:** 08-7522-9

**Issue Date:** 08/23/18

**Version Number:**

12.04

**Supersedes Date:**

08/22/18

**Reason for Reissue**

Conversion to GHS format SDS.

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for

<b>3M™ Fast Cure Auto Glass Urethane, PN 08566, 08689, 08690</b>	<b>08/23/18</b>
--	-----------------

user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**