SEALANTS

CRL7708 WINDSHIELD AND BODY SEALANT

PRODUCT NAME:

CRL 7708 Windshield and Body Sealant

SEALANTS Butyl Sealant

PRODUCT DESCRIPTION

CRL 7708 is a non-hardening, non-drying, water resistant sealer for rubber set windshields and backlites.

- · Non-hardening, non-drying remains flexible
- · Absorbs expansion, shock and vibration
- · Easy clean-up, wipe with dry rag

BASIC USE

CRL 7708 can be used between the gasket and the body of the automobile as well as between the glass and the gasket to seal out moisture, dust and air.

INSTRUCTIONS FOR USE

- 1. Cut nozzle to desired bead size.
- Clean surfaces to be sealed of grease, oil and foreign matter.
- For windshields, flow small bead into gasket channel cavity.
- 4. For body joints and seams, apply uniform bead to clean surfaces.
- 5. DO NOT THIN.

TABLE 1 - PHYSICAL PROPERTIES	
Property/Test Methods	Value
Base Polymer	Butyl
Color	Black
Solids, by weight	85%
Specific Gravity	1.30
Sag Resistance (ASTM D2202)	0.15"
Maximum @ 158	°F (70°C)
Heat Resistance 1 Month@158°F (70°C)	.Excellent
U.V. Resistance 1 Month in QUV	Excellent

NOTE: The foregoing information is published as general information only. The listed properties and performance characteristics are approximate values and are not part of the product specification.

SAFETY PRECAUTIONS

For all CRL products, and for other products used in conjunction with CRL products, user must follow individual product data sheet and Material Safety Data Sheets (M.S.D.S.) for health and safety precautions. Always use protective eyewear.

CLEAN UP


Use CRL 2032 General Purpose Solvent.

LIMITATIONS

- 1. Should not be used when installation calls for urethane adhesive on gasket.
- 2. No adhesive qualities for use sealant only.

PACKAGING

10.5 fl.oz. (310 ml) cartridge.



March 2003 (Supercedes December 2001)

PAGE 1 OF 2 AVD3749-REV06/03

TECHNICAL SERVICE

Complete technical information and literature is available from C.R. Laurence Co., Inc. Any technical advice furnished by the company or any representative of the company concerning any use or application of any sealant is believed to be reliable, but the company makes no warranty, expressed or implied, for any use or application for which such advice is furnished.

LIMITED WARRANTY NOTICE

Los Angeles, California

2503 E Vernon Avenue

Los Angeles, CA 90058-1897

Phone: (323) 588-1281

Fax: (323) 581-6522

Dallas, Texas

2080 Lone Star Drive

Dallas, TX 75212-6390

Phone: (214) 634-7305

Fax: (214) 631-6519

Chicago Area

1501 Tonne Road

Elk Grove Village, IL 60007-5069

Phone: (847) 437-8320

Fax: (847) 437-8447

San Francisco / Oakland Area

33200 Dowe Avenue

Union City, CA 94587-2013

Phone: (510) 475-1000

Fax: (510) 475-1404

Atlanta, Georgia

600 Wharton Drive

Atlanta, GA 30336-4040

Phone: (404) 696-3445

Fax: (404) 696-3386

CRL and its manufacturer warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products but also upon many factors beyond our control in the application process. Therefore, except for such replacement or refund CRL and its manufacturers make no warranty or guarantee, expressed or implied, including warranties of fitness merchantability, respecting its products. CRL and its manufacturers shall have no other liability with respect thereto. User shall determine the suitability of the product for his intended use and assume all risks and liability in

connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the CRL Product Manager.

COOPERATIVE TESTING

Materials submitted for testing should be sent to:

C.R. Laurence Co., Inc. **Technical Sales Department** PO Box 58923 Los Angeles, CA 90058-0923

This program is intended to eliminate potential field problems by pretesting CRL construction sealants with sample of the building materials on which the sealant will be applied. The test will aid in determining the proper surface preparation method, effective solvents for cleaning and whether priming is necessary to achieve optimum adhesion. Following this procedure will remove many of the unknown variables which affect field success.

Test samples of substrates should be identified as to manufacturer, origin, designed use building project, person and firm originating the request. Appropriate sketches or drawings showing the intended use can be helpful.

C.R. LAURENCE CO., INC. LOCATIONS **United States**

New York City Area

211 County Avenue Secaucus, NJ 07094-2006 Phone: (201) 770-1077 Fax: (201) 770-1599

Boston Area

97 Robert Treat Paine Drive Taunton, MA 02780-1267 Phone: (508) 880-5600 Fax: (508) 880-5775

Orlando, Florida

6950 Presidents Drive Orlando, FL 32809-5668 Phone: (407) 857-7900 Fax: (407) 857-7766

Denver, Colorado

4770 Joliet Street Denver, CO 80239-2513 Phone: (303) 373-9988 Fax: (303) 373-0884

Seattle Area

23000 64th Avenue SW Kent, WA 98032-1838 Phone: (253) 850-5800 Fax: (253) 813-1818

Cleveland area

March 2003 (Supercedes December 2001)

SEALANTS

31600 Carter Street Solon, OH 44139-3551 Phone: (440) 248-0003 Fax: (440) 248-0120

Philadelphia Area

1511 Lancer Drive Moorestown, NJ 08057-4232 Phone: (856) 727-1022 Fax: (856) 727-3299

Phoenix, Arizona

640 S. 54th Avenue Phoenix, AZ 85043-4731 Phone: (602) 269-7500 Fax: (602) 269-7600

Europe C.R. Laurence Europe GmbH

Boschstrasse 6 D-40880 Ratingen B Düsseldorf, Germany Phone: 49-2102-74-28-38 Fax: 49-2102-74-28-34

₩ CRL Canada ₩

Vancouver Area

11920 Horseshoe Way Richmond, BC V7A 4V5 Phone: (604) 448-9344 Fax: (604) 448-9322

Montreal Area

8200 Rue Des Bâtisseurs Anjou, QC H1J 3B3 Phone: (514) 352-3300 Fax: (514) 352-1017

Toronto Area

65 Tigi Court Concord, ON L4K 5E4 Phone: (905) 303-7966 Fax: (905) 303-7965

Calgary, Alberta

4200 116 Avenue SE Calgary, AB T2Z 4B5 Phone: (403) 250-5783 Fax: (403)291-3260

AVD3749-6/03

PAGE 2 OF 2