

MATERIAL SAFETY DATA SHEET

Company Name: C.R. LAURENCE CO., INC.
Address: 2503 E. VERNON AVE.
City / State / Zip: LOS ANGELES / CA / 90058
US-CHEMTREC Phone(I): (800)424-9300
US-CHEMTREC Phone(II): (703)527-3887
CAN-CANUTEC Phone: (613)996-6666
Vendor Update: 8/21/2000
Date Prepared: 6/5/2003
MSDS Number: WFSR100 ;

I. CHEMICAL PRODUCT IDENTIFICATION

Product Name: UNIVERSAL FILLER STRIP
HMIS Ratings:
 Health: Minimal(0)
 Flammability: Slight(1)
 Instability/Reactivity: Minimal(0)
 Personal Protective Equipment: A
NFPA Ratings:

II. COMPOSITION, INFORMATION ON INGREDIENTS

Chemical Ingredients	C.A.S. Number	% By Weight	ACGIH TLV TWA/STEL	OSHA PEL TWA/STEL	Other TWA/STEL	LD50	LC50
MIXTURE (POLYVINYL CHLORIDE (PVC)/VINYL COMPOUNDS)			NOT AVAILABLE	NOT AVAILABLE			
Notes							

III. HAZARDS IDENTIFICATION PRIMARY ROUTE OF ENTRY

Eyes: DUST AND FUMES MAY BE IRRITATING TO THE EYES.
Skin: DUST AND FUMES MAY CAUSE SLIGHT IRRITATION TO SENSITIVE PEOPLE.
Ingestion: NOT A LIKELY ROUTE OF EXPOSURE.
Inhalation: FUMES FROM PROCESS MAY BE IRRITATING TO THE MUCOUS MEMBRANES OF THE RESPIRATORY TRACT.
Other: PERMISSIBLE CONCENTRATIONS (AIR): NOT AVAILABLE.

IV. FIRST AID MEASURES

Eyes: IF SYMPTOMS DEVELOP, FLUSH EYES WITH ADEQUATE STREAM OF WATER. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.
Skin: WASH THOROUGHLY WITH SOAP AND WATER.
Ingestion: NO EFFECT EXPECTED. IF LARGE AMOUNTS INGESTED, SEEK MEDICAL ATTENTION.
Inhalation: REMOVE TO FRESH AIR IF SYMPTOMS DEVELOP.

V. FIRE FIGHTING MEASURES

Flash Point: 590° F (310 °C)
Lower Flammability Limit: NOT AVAILABLE
Upper Flammability Limit: NOT AVAILABLE

Extinguishing Agents: WATER, DRY CHEMICAL

Unusual Fire or Explosion DECOMPOSITION BY BURNING (GENERATING HCL GAS).

Hazards:

Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SELF CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING IN FIRE CONDITIONS.

Other: AUTOIGNITION TEMPERATURE (ASTM D1929): +850°F (454° C)

VI. ACCIDENTAL RELEASE MEASURES

Containment/Cleanup: CAREFULLY SWEEP OR VACUUM UP AND PLACE IN MARKED CONTAINERS FOR REUSE OR RECYCLE.

VII. HANDLING AND STORAGE

Other: STORE IN CLOSED CONTAINERS IN A COOL, DRY WELL VENTILATED AREA, AWAY FROM DIRECT HEAT.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: WEAR SAFETY GLASSES WITH SIDE SHIELDS (ANSI 87.1,1979)

Skin: GLOVES: NOT NECESSARY, BUT SENSITIVE PEOPLE SHOULD WEAR THEM.

Respiratory: A NIOSH/MSHA APPROVED RESPIRATOR SHOULD BE WORN IF THE PEL IS EXCEEDED.

Engineering: GENERAL ROOM VENTILATION

IX. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: TRANSPARENT, WHITE, COLORED, OR BLACK

Solubility in Water: NEGLIBLE

Specific Gravity: FROM .99 – 1.50 DEPENDING ON FORMULATION

X. STABILITY AND REACTIVITY

Stability: STABLE

Hazardous Polymerization: WILL NOT OCCUR

Hazardous Decomposition CO, CO₂, HCL

Products:

Incompatible Products: ACETAL AND/OR ACETAL COPOLYMERS OR WITH AMINE CONTAINING MATERIALS DURING PROCESSING.

Conditions To Avoid: EXCESSIVE HEAT FOR PROLONGED PERIODS.

XI. TOXICOLOGICAL INFORMATION

XII. ECOLOGICAL INFORMATION

XIII. DISPOSAL CONSIDERATIONS

Disposal Method: DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GOVERNMENT REGULATIONS.

XIV. TRANSPORT INFORMATION**D.O.T. Shipping Name:** NOT AVAILABLE**D.O.T. Hazard Class:** NOT AVAILABLE**XV. REGULATORY INFORMATION****TSCA Status:** ALL INGREDIENTS AND/OR MATERIALS USED IN THE MANUFACTURE OF OUR VINYL COMPOUNDS HAVE BEEN REGISTERED IN ACCORDANCE TO THE RULES OF THE TOXIC SUBSTANCE CONTROL ACT.

EPA Sara Title III Chemical Listings: IMMEDIATE (ACUTE) HEALTH: NO
DELAYED (CHRONIC) HEALTH: NO
FIRE HAZARD: NO
REACTIVE HAZARD: NO
SUDDEN RELEASE OF PRESSURE: NO

XVI. OTHER INFORMATION**WARRANTY INFORMATION**

THIS INFORMATION IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.