

SAFETY DATA SHEET

SDS Number: 00070041001

Revision Date: 6/19/2015

	<h2>Safety Data Sheet</h2>	<p>24 Hour Emergency Phone Numbers Medical/Poison Control: In U.S.: Call 1-800-222-1222</p> <p>Outside U.S.: Call your local poison control center</p> <p>Transportation/National Response Center: 1-800-535-5053 1-352-323-3500</p> <p>NOTE: The National ResponseCenter emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.</p>
---	----------------------------	---

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this MSDS are further described in Section 16.

1. Identification

This Safety Data Sheet is available in American Spanish upon request.
Los Datos de Seguridad pueden obtenerse en Espanol si lo requiere.

Product Name:	DAP Weldwood FRP Adhesive	Revision Date:	6/19/2015
CRL CATALOG NUMBER:	DAP60480		
Product UPC Number:	60480, 60481	Supersedes Date:	New SDS
Product Use/Class:	Construction Adhesive	SDS No:	00070041001
Manufacturer:	DAP Products Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 888-327-8477 (non - emergency matters)		
Preparer:	Regulatory Department		

2. Hazards Identification

EMERGENCY OVERVIEW: May cause eye, skin, nose, throat and respiratory tract irritation.

GHS Classification

Not a hazardous substance or mixture.

Symbol(s) of Product

None

Signal Word

Not a hazardous substance or mixture.

3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Limestone	1317-65-3	50-75	GHS03	H270
Urea	57-13-6	1.0-2.5	GHS03	H270
Quartz	14808-60-7	0.1-1.0	GHS03-GHS07	H270-302

Page 1 of 6

SDS Number: 00070041001

Revision Date: 6/19/2015

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - INHALATION: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: In case of contact, wash skin immediately with soap and water.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: 465 <undefined>

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Scrape up dried material and place into containers. Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Construction and repair activities can adversely affect indoor air quality. Consult with occupants or a representative (i.e. maintenance, building manager, industrial hygienist, or safety officer) to determine ways to minimize impact. Do not sand, dry sweep, dry scrape, drill, saw, beadblast, mechanically chip, pulverize or otherwise machine existing resilient flooring, backing, lining felt, or asphaltic "cut-back" adhesives. These products may contain either asbestos fibers or crystalline silica. Avoid creating dust. Inhalation of such dust is a cancer and respiratory tract hazard. See current edition of the Resilient Floor Covering Institute's publication "Recommended Work Practices for Removal of Resilient Floor Coverings", for detailed information and instructions addressed to the task of removing all resilient floor covering materials.

STORAGE: Avoid excessive heat and freezing. Do not store at temperatures above 120 degrees F. Store away from caustics and oxidizers. Keep containers tightly closed.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
Limestone	N.E.	N.E.	15 mg/m ³ TWA total dust, 5 mg/m ³ TWA respirable fraction	N.E.
Urea	N.E.	N.E.	N.E.	N.E.
Quartz	0.025 mg/m ³ TWA respirable fraction	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: National Institute for Occupational Safety and Health (NIOSH) has recommended that the permissible exposure limit be changed to 50 micrograms respirable free silica per cubic meter of air (0.05 mg/m³) as determined by a full shift sample up to 10-hour work shift. Respirator use is not expected to be necessary under normal conditions of handling. In emergency situations, use of a NIOSH-approved respirator may be required. A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.



SKIN PROTECTION: Wear rubber gloves.



EYE PROTECTION: Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Not required under normal use.



HYGIENIC PRACTICES: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

9. Physical and Chemical Properties

Appearance:	Tan	Physical State:	Paste
Odor:	Little or No	Odor Threshold:	Not Established
Density, g/cm ³ :	1.55 - 1.55	pH:	Between 7.0 and 12.0
Freeze Point, °C:	Not Established	Viscosity (mPa.s):	Not Established
Solubility in Water:	Not Established	Partition Coeff., n-octanol/water:	Not Established
Decomposition Temperature, °C:	Not Established	Explosive Limits, %:	N.I. - N.I.
Boiling Range, °C:	N.I. - N.I.	Auto-Ignition Temperature, °C:	Not Established
Minimum Flash Point, °C:	93.3	Vapor Pressure, mmHg:	No Information
Evaporation Rate:	Slower Than n-Butyl Acetate	Flash Method:	Seta Closed Cup
Vapor Density:	Heavier Than Air	Flammability:	No Information
Combustibility:	Does not support combustion		

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Excessive heat and freezing.

INCOMPATIBILITY: Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., CO_x, NO_x.

11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: Vapors may be irritating to eyes, nose, throat, and lungs. Inhalation of vapors in

high concentration may cause mild irritation of respiratory system (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Prolonged or repeated contact with skin may cause mild irritation.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Direct eye contact may cause irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Under normal use conditions, this product is not expected to cause adverse health effects. Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury.

CARCINOGENICITY: No Information

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Repeated or prolonged exposure may cause irritation of eyes and skin. The International Agency for Research on Cancer (IARC) has determined that crystalline silica in the form of quartz or cristobalite that is inhaled from occupational sources is carcinogenic to humans (Group 1- carcinogenic to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (published in June 1997) in conjunction with the use of these materials. The National Toxicology Program (NTP) classifies respirable crystalline silica as "known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (Group A2). Breathing dust containing respirable crystalline silica may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may have the following serious chronic health effects: Excessive inhalation of respirable dust can cause pneumoconiosis, a respiratory disease, which can result in delayed, progressive, disabling and sometimes fatal lung injury. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function. Smoking exacerbates this disease. Individuals with pneumoconiosis are predisposed to develop tuberculosis. There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by fibrosis of the lungs, skin and other internal organs) and kidney disease.

PRIMARY ROUTE(S) OF ENTRY: Inhalation, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
1317-65-3	Limestone	6450 mg/kg Rat	>2000 mg/kg	>20 mg/L
57-13-6	Urea	8471 mg/kg Rat	N.I.	N.I.
14808-60-7	Quartz	500 mg/kg Rat	>2000 mg/kg	>20 mg/L

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

13. Disposal Information

DISPOSAL INFORMATION: This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

SDS Number: 00070041001

Revision Date: 6/19/2015

DOT UN/NA Number: None
 DOT Proper Shipping Name: Not Regulated
 DOT Technical Name: N.A.
 DOT Hazard Class: N.A.
 Hazard SubClass: N.A.
 Packing Group: N.A.

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard, Chronic Health Hazard

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

CALIFORNIA PROPOSITION 65 CARCINOGENS AND REPRODUCTIVE TOXINS

CALIFORNIA PROPOSITION 65: No Information

International Regulations: As follows -

CANADIAN WHMIS:

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class Consumer Commodity

16. Other Information

Revision Date: 6/19/2015 Supersedes Date: New MSDS
 Reason for revision: HazCom2012/GHS Conversion
 Datasheet produced by: Regulatory Department

HMIS Ratings:

Health:	1	Flammability:	0	Reactivity:	0	Personal Protection:	X
---------	---	---------------	---	-------------	---	----------------------	---

VOC Less Water Less Exempt Solvent, g/L: 31.7

VOC Material, g/L: 16

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 0.4

SDS Number: 00070041001

Revision Date: 6/19/2015

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H270 May cause or intensify fire; oxidiser.
H302 Harmful if swallowed.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS03



GHS07



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.