


COMPANY NAME _____	PHONE _____
CONTACT _____ ACCOUNT NO. _____	FAX _____
JOB NAME _____	EMAIL _____

☐ **QUOTE** ☐ **ORDER P.O. #** _____ **DATE** _____

STANDARD PROFILE DIMENSIONS				
SERIES	THICKNESS	STILE	TOP RAIL	BOTTOM RAIL
400T MEDIUM STILE THERMAL DOOR	1-3/4"	4-1/4"	4-5/16"	7-1/4"
400AT MEDIUM STILE ADVANCE THERMAL DOOR	1-3/4"	4-1/4" (Foam Filled)	4-5/16" (Foam Filled)	7-1/4" (Foam Filled)
OPTIONAL				10"



Use the Door Swing Chart to determine how the door(s) should be handed.

APPLICATION : MODERATE TO HEAVY TRAFFIC

DOOR STILE APPLICATION

- ☐ 400T Medium Stile Thermal Door
- ☐ 400AT Medium Stile Advance Thermal Door

DOOR FINISH

- ☐ 11 - Clear Anodized Class I - Standard
- ☐ 22 - Dark Bronze / Black Anodized Class I
- ☐ 52 - Bone White 70% KYNAR® (2-Coat)
- ☐ 71 - Standard 70% KYNAR® (2-Coat)
Standard Color per Chart- Specify _____
- ☐ 71 - Custom 70% KYNAR® (2-Coat) - Specify _____
- ☐ 71 - Custom 70% KYNAR® (3-Coat) - Specify _____

DOOR OPENING SIZE

- ☐ 36" x 84"
- ☐ Custom Single _____
Door Tag # _____
- ☐ 72" x 84"
- ☐ Custom Pair _____
Door Tag # _____
Maximum Leaf Size 48" x 96"

GLASS STOP

- ☐ 1" (25 mm) Square Glass Stops

TOP RAIL - INCLUDES GLASS STOP

- ☐ 4-5/16" HT101 (Standard)
- ☐ 2-7/8" HT201
- ☐ 6" WT201

BOTTOM RAIL - INCLUDES GLASS STOP

- ☐ 7-1/4" JT650 (Standard)
- ☐ 4-5/16" HT101
- ☐ 6" WT201
- ☐ 10" WT196

MUNTINS - INCLUDES GLASS STOP

- ☐ 3-5/8" (HT202)
- ☐ 5-1/16" (MT101)
- ☐ 6-3/4" (MT201)
- ☐ 8" (JT650)
- ☐ 10-3/4" (MT196)

DOOR SWING

- | | QTY |
|--|-----------|
| ☐ LHR Hinge Left Swing Out | _____ ea. |
| ☐ RHR Hinge Right Swing Out | _____ ea. |
| ☐ LH Hinge Left Swing In | _____ ea. |
| ☐ RH Hinge Right Swing In | _____ ea. |
| ☐ PAIR Swing In | _____ ea. |
| ☐ PAIR Swing Out | _____ ea. |

DOOR HINGING

- ☐ Top/Bottom and Intermediate Offset Pivots (OP500/DH010)
- Additional Pivot ☐ DH010
Add _____ per Door
- ☐ 1-1/2 Pair Butt Hinges (DH009)
Add _____ per Door
- ☐ Continuous Geared Hinge (DH492)
- ☐ By USALUM
- ☐ By Customer
- ☐ Prep and Supply
- ☐ Prep Only (Selection Above)
- ☐ No Prep

HARDWARE FINISH

- | | |
|--|----------------|
| • Clear | 11, 12, 52, 71 |
| • Bronze | 22 |
| ☐ Specify _____ | |

DOOR SWEEP

- ☐ Yes ☐ No
- ☐ Exposed Fasteners
- ☐ Concealed Fasteners

LOCKING OPTIONS

- ☐ MS Hookbolt With Two Cylinders - **STD**
- ☐ Long Throw Deadlock With Cylinders
- ☐ 3-Point Locking @ Pair With Cylinders
- ☐ Latch/Deadlock (DH189) With Cylinders
- ☐ Thumbturn in Lieu of Cylinder
- ☐ Latchlock (DH002)
- ☐ Cylinder (Ext.) ☐ Cylinder (Int.)
- ☐ Thumbturn (Int.)
- ☐ Lock Indicator
- ☐ Cylinder Guard
- ☐ Flushbolts (DH008)
- ☐ Paddle Handle
- DH569 Lever Handle
 - ☐ Interior ☐ Back to Back
- CRL DL2150 Lever Handle
 - ☐ Interior ☐ Back to Back
- ☐ Electric Strike
- ☐ Prep and Supply ☐ Prep Only

PANIC DEVICES

- ☐ Jackson 1285 Concealed Vertical Rod Panic
- ☐ Jackson 1295 Rim Panic Device
- ☐ Jackson 2086 Concealed Vertical Rod Panic
- ☐ Jackson 2095 Rim Panic Device
- ☐ Jackson 1085 Concealed Vertical Rod Panic
- ☐ Jackson 1095 Rim Panic Device
- ☐ Adams-Rite 8400 Mortise Panic Device
- ☐ Adams-Rite 8600 Concealed Vertical Rod Panic
- ☐ Adams-Rite 8800 Rim Panic Device
 - ☐ with cylinder ☐ cylinder by others (prep only)
- ☐ Von Duprin® 33AE ☐ Von Duprin® 35AE
- ☐ Von Duprin® 3327AE ☐ Von Duprin® 3527AE
- ☐ Von Duprin® 3347AE ☐ Von Duprin® 3547AE
- Outside Von Duprin Trim
 - ☐ 360L ☐ 360T ☐ 388NL
 - ☐ with cylinder ☐ cylinder by others (prep only)

- ☐ Exit Only
- ☐ By USALUM
- ☐ By Customer
- ☐ Prep and Supply
- ☐ Prep Only (Selection Above)

FOR OFFICE USE ONLY

TAKEN BY: _____

PRICED BY: _____

EDITED BY: _____

PUSH/PULL HARDWARE ☐ Standard Push/Pull ☐ Offset Pulls ☐ None _____ ☐ Custom ☐ By USALUM ☐ By Customer ☐ Prep and Supply ☐ Prep Only NOTE: Prep Only Requires Manufacturer's Name , Model, and Template Manufacturer: _____ Model: _____ _____	DOOR CLOSER ☐ O.H. Concealed (Offset-Prep Only) ☐ Standard Jackson Closer (Supply) ☐ 90° ☐ 105° Hold Open ☐ Yes ☐ No ☐ CRL Surface Mount Closer (Supply) ☐ Drop Plate ☐ Door Stop/Holder Degree _____ ☐ No Closer Required ☐ Custom ☐ By USALUM ☐ By Customer ☐ Prep and Supply ☐ Prep Only NOTE: Prep Only Requires Manufacturer's Name , Model, and Template Manufacturer: _____ Model: _____ _____	FRAME SYSTEM Series IT451 2" x 4-1/2" ☐ Open Back Subframe ☐ 1" x 4-1/2" (Thermal) Tubular Only FRAME TYPE ☐ Up and Over (No Transom) ☐ 126" (3.2 m) High With Transom ☐ Frame Only ☐ Door Only (No Frame) ☐ Custom _____
CLEARANCES/THRESHOLD Clearance from Bottom of Door to Finish Floor ☐ 11/16" Standard (Required for 0P500 Pivot Set) ☐ Custom Clearance Specify _____ • TT245 1/2" Threshold		

ADDITIONAL NOTES OR SKETCHES	

APPROVED BY _____ DATE _____

FOR OFFICE USE ONLY	
TAKEN BY:	_____
PRICED BY:	_____
EDITED BY:	_____

NOTE: PLEASE DOWNLOAD FORM TO SUBMIT. DO NOT FILL FORM ONLINE.
Email completed form to us_alum@usalum.com.
Fax checklist to U.S. Aluminum Technical Sales at (877) 883-7547
To review call (800) 627-6440. This form is available online at usalum.com.