

Base Shoe Quote/Order Request Form

Date _____

Name _____
 Email _____
 Phone Number _____

Company _____
 Account Number _____
 Job Name _____

Utilize this form to assist you in covering the details required to complete a Base Shoe installation. Going through this exercise should prevent you from overlooking any details related to your installation.

IMPORTANT: Depending on the complexity of your project, one or more of the following may be required to accurately order: sketches or drawings of your particular application with dimensions; printed architectural drawings or CAD files; photos of the job site conditions (digital images are preferable).

NOTE: Please download and submit completed form to railings.archmetals@crlaurence.com. A final sign off is required prior to any custom fabrication.

TYPE OF ATTACHMENT

- Base Shoe to Concrete
- Base Shoe to Weld Block
- Base Shoe to Steel Channel or Angle
- Base Shoe Embedded in Concrete (Flush Set)
- Base Shoe to Steel Embedment Strip

STOCK FINISH

- Brushed Stainless Steel US32D
- Polished Stainless Steel US32
- Polished Brass US3
- Satin Brass US4
- Satin Anodized US28
- Dark Bronze Anodized 313
- Custom Finish: _____

ATTACHMENT FASTENERS AND ACCESSORIES

- Wedge-Bolt Anchors and Washers (for Concrete)
- 1/2"-13 Socket Head Cap Screws (for Steel)
- HSL3 Expansion Anchors (for Concrete)
- Hex Head Cap Screws
- Weld Blocks (for Steel) Drain Blocks
- Nylon Allen Screws (Protects Steel Embedment Threads)

CLADDING LENGTH

- 120" (3.05 m) Stock Length
- Custom Length up to 168" (4.26 m) (Cuts, L.H. Miter or R.H. Miter)

STYLE OF BASE SHOE AND GLASS SECURING METHOD

- 8B Series for 1/2" (12 mm) Monolithic Tempered Glass
- 8B Series for 5/8" (15 mm) Monolithic Tempered Glass
- 8B Series for 3/4" (19 mm) Monolithic Tempered Glass
- 9BL Series for 9/16" (13.5 mm) Laminated Tempered Glass
- 9BL Series for 11/16" (17.5 mm) Laminated Tempered Glass
- 9BL Series for 27/32" (21.5 mm) Laminated Tempered Glass

CLADDING ACCESSORIES

- End Caps
- Mitered Corner Sets
- Welded End Caps
- Cladding Securing Tape
- Cladding Securing Silicone Sealant

BASE SHOE LENGTH

- 120" (3.05 m) 240" (6.10 m)
- Custom Length (Cuts, L.H. Miter or R.H. Miter)

BASE SHOE HOLE FABRICATION

- No Fabrication Drill and Counter Bore on 12" (305 mm) Centers
- Drill and Counter Bore on 6" (152 mm) Centers
- Other _____

GLASS SECURING ACCESSORIES

- Taper-Loc® Dry Glaze 1/2" and 3/4" (12 and 19 mm) Monolithic Tempered Glass
- Taper-Loc® Dry Glaze 3/8" (10 mm) Monolithic Tempered Glass
- Taper-Loc® Dry Glaze 27/32" and 1-1/16" (21.52 and 25.52 mm) Laminated Tempered Glass
- Taper-Loc® Dry Glaze 9/16" (13.52 mm) Laminated Tempered Glass
- Taper-Loc® Dry Glaze 11/16" (17.52 mm) Laminated Tempered Glass
- Wet Glaze 1/2" (12 mm) Setting and Centering Blocks
- Wet Glaze 5/8" (16 mm) Setting and Centering Blocks
- Wet Glaze 3/4" (19 mm) Setting and Centering Blocks
- 1/4" (6 mm) Spacing and Sealing Pads for 1/2" (12 mm) Glass
- 1/4" (6 mm) Spacing and Sealing Pads for 3/4" (19 mm) Glass
- 1/4" (6 mm) Rigid Rubber Spacing Blocks for 1/2" (12 mm) Glass
- 1/4" (6 mm) Rigid Rubber Spacing Blocks for 3/4" (19 mm) Glass
- Base Shoe Gasket [for 1/2" (12 mm) and 3/4" (19 mm) Glass Only]
- Expanding Cement

CLADDING REQUIRED

- Yes No

Product Selection: (Fill in Appropriate Areas for All Products That Will Be Required for the Job)

PRODUCT	CAT. NO.	QTY.
Base Shoe		
Taper-Loc® Sets		
Expanding Cement		
Setting/Centering Blocks		
Spacing/Sealing Pads		
Rigid Rubber Spacers		
Base Shoe Gasket		
Cladding Stock Lengths		
End Caps		
Corners		
Fasteners		
Tape		
Silicone Sealant		
Installation Tools		

RESET BUTTON

Please submit to: railings.archmetals@crlaurence.com