

SAFETY DATA SHEET

Date of issue: 06/22/2015 Revision date: 10/09/2018

Version: 2.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Palmer Mirro-Mastic® Bond

CRL Catalog Number : PMB401GL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Primer

1.3. Details of the supplier of the safety data sheet

Palmer Products Corporation 146 St. Matthews Avenue Louisville, KY 40207 - USA T 502.893.3668

palmer@mirro-mastic.com

1.4. Emergency telephone number

Medical Emergency Phone Number : (CHEMTREC): 1-800-424-9300 (24 Hours)

Transport Emergency Phone Number : (CHEMTREC): 1-800-424-9300 (24 Hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquid 2
Aspiration toxicity 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)



③

HS02

GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Highly flammable liquid and vapor. May be fatal if swallowed and enters airways

Precautionary statements (GHS-US) : Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance

with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

SDS1157_PMB401GL_10/18



32 **Mixture**

Name	Product identifier	%
Naphtha, petroleum, hydrotreated heavy	(CAS-No.) 64742-48-9	70 - 80
Asphalt, oxidized	(CAS-No.) 64742-93-4	20 - 30

^{*}Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First aid measures

Description of first aid measures

First-aid measures after inhalation

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

Get medical attention immediately.

In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and First-aid measures after skin contact

shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

First-aid measures after eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists,

get medical attention.

If swallowed, do NOT induce vomiting. Never give anything by mouth to an unconscious person. First-aid measures after ingestion

Immediately call a POISON CENTER or doctor/physician.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory tract irritation.

Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear Symptoms/injuries after eye contact

production, with possible redness and swelling.

May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause Symptoms/injuries after ingestion

chemical pneumonitis. May cause stomach distress, nausea or vomiting.

Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Powder, water spray, foam, carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream

Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor. Products of combustion may include, and are not limited to:

oxides of carbon.

Explosion hazard : May form flammable/explosive vapour-air mixture.

5.3. **Advice for firefighters**

: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection Protection during firefighting

(SCBA). Cool closed containers exposed to fire with water.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to General measures

unnecessary and unprotected personnel. Eliminate sources of ignition.

Methods and material for containment and cleaning up 6.2.

For containment Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container.

Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment

Methods for cleaning up : Scoop up material and place in a disposal container. Vapors may be heavier than air and may travel

along the ground to a distant ignition source and flash back. Provide ventilation.

Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Take precautionary measures against static discharge. Use only non-sparking

tools. Use only in well-ventilated areas.

crlaurence.com Page 2 of 5



7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

: Keep out of the reach of children. Store in a well-ventilated place. Keep cool. Keep container tightly Storage conditions

closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

Control parameters

Asphalt, oxidized (64742-93-4)

Not applicable

Naphtha, petroleum, hydrotreated heavy (64742-48-9)

Not applicable

Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below

recommended exposure limits.

Hand protection : Wear suitable gloves.

Safety glasses or goggles are recommended when using product. Eye protection

Skin and body protection Wear suitable protective clothing.

: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection Respiratory protection

must be based on known or anticipated exposure levels, the hazards of the product and the

safe working limits of the selected respirator.

Maintain levels below Community environmental protection thresholds. Environmental exposure controls

Other information Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully

before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state : Liquid

: Black Thin Liquid Appearance

Colour : Black Odour Solvent

Odour threshold No data available рΗ No data available Melting point No data available Freezing point : No data available

Boiling point 264 2 °F Flash point 48 °F

: No data available Relative evaporation rate (butylacetate=1) Flammability (solid, gas) Flammable Explosive limits : No data available Explosive properties No data available Oxidising properties No data available Vapour pressure : No data available

Relative density 0.78

Relative vapour density at 20 °C No data available Solubility : No data available Partition coefficient: n-octanol/water No data available Loa Kow : No data available Auto-ignition temperature No data available Decomposition temperature : No data available : No data available Viscosity Viscosity, kinematic < 20.5 cSt : No data available Viscosity, dynamic

crlaurence.com Page 3 of 5



9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition.

10.5. Incompatible materials

Asphalt oxidized (64742.93.4)

Strong oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified.

Aspnait, oxidized (64/42-93-4)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
Naphtha, petroleum, hydrotreated heavy (64742-48-9)		
LD50 oral rat	> 6000 mg/kg	
LD50 dermal rabbit	> 3160 mg/kg	
LC50 inhalation rat	> 8500 mg/m³ (Exposure time: 4 h)	
Skin corrosion/irritation	: Based on available data, the classification criteria are not met.	
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.	
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.	
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.	
Carcinogenicity	: Based on available data, the classification criteria are not met.	

Asphalt, oxidized (64742-93-4)		
IARC group	2A - Probably carcinogenic to humans	
In OSHA Hazard Communication Carcinogen list	Yes	

Reproductive toxicity : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure) : Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure) : Based on available data, the classification criteria are not met.

Aspiration hazard : May be fatal if swallowed and enters airways.

Symptoms/injuries after inhalation : May cause respiratory tract irritation.

Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear

production, with possible redness and swelling.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause

chemical pneumonitis. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Naphtha, petroleum, hydrotreated heavy (64742-48-9)		
LC50 fish 1	2200 mg/l (Exposure time: 96 h - Species: Pimephales promelas)	

crlaurence.com Page 4 of 5



12.2. Persistence and degradability

Palmer Mirro-Mastic® Bond
Persistence and degradability Not established.

12.3. Bioaccumulative potential

Palmer Mirro-Mastic® Bond

Bioaccumulative potential Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal

regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Handle empty containers with care because residual vapours are flammable.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

14.1. UN number

UN-No.(DOT) : UN1993

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Flammable liquid, n.o.s. (Petroleum distillates)

Transport hazard class(es) (DOT) : 3

Hazard labels (DOT)



Packing group (DOT) : III

Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/ or reproductive harm.

SECTION 16: Other information

 Date of issue
 : 06/07/2018

 Revision date
 : 10/09/2018

 Version
 : 2.1

 Other information
 : None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

crlaurence.com Page 5 of 5