

Blumcraft® Entice® Series Entrance System



All-Glass Aesthetics + Thermal Performance

Entice represents an evolution of glass entrances. The groundbreaking system features ultra-narrow 1-1/8" vertical stiles that produce clean glass spans and striking all-glass visuals. It also presents a thermally broken frame and 1" insulating glass that together deliver U-factors as low as 0.43 to meet stringent energy codes. The result is a premium glass entrance system that doesn't compromise aesthetics for performance.

A distinct quality of the Entice Series Entrance System is its ability to support tubular panic devices and other types of door handle hardware directly on 1" dual-glazed insulating glass units. This is achieved with precision-engineered through-glass fittings. The capability creates a floating-on-air aesthetic that enhances the system's streamlined design.

With an increased emphasis on thermal performance, the future of glass entrances is double-glazed insulating units. Entice is at the forefront, delivering low U-factors while simultaneously producing the in-demand, all-glass aesthetics of Herculite[®] style doors.

Aesthetics

- Ultra-narrow 1-1/8" vertical stiles
- System depth of only 2-1/2"
- Provides monolithic, heavy-glass door visuals
- Premium cladding in customizable finishes
- Handle hardware mounts directly onto insulating glass
- Clamping mechanism eliminates glass stop break lines
- Doors can be specified up to 10 feet high

Performance

- Thermally broken frame and threshold
- Utilizes 1" insulating glass
- U-factors as low as 0.43 for doors
- NFRC rated system
- Complies with California Title 24
- Meets ASHRAE 90.1 air infiltration requirements
- Passes ASTM E331 water penetration testing

