

# CRL | Adjustable Standoff Glass Height Limitations

## Allowable heights to withstand 50 plf top load Use 3/4" (19 mm) to 27/32" (21 mm) glass

### 2 Standoff Pairs With 4" Spacing

<b>Glass Width (in)</b>	36	48	60	72
<b>Allowable Height (in)</b>	50	42	42	36

### 3 Standoff Pairs With 4" Spacing

<b>Glass Width (in)</b>	36	48	60	72
<b>Allowable Height (in)</b>	50	50	42	36

### 2 Standoff Pairs With 6" Spacing

<b>Glass Width (in)</b>	36	48	60	72
<b>Allowable Height (in)</b>	50	42	42	39

### 3 Standoff Pairs With 6" Spacing

<b>Glass Width (in)</b>	36	48	60	72
<b>Allowable Height (in)</b>	50	50	42	36

## Allowable heights to withstand 200 lb concentrated load Use 3/4" (19 mm) to 27/32" (21 mm) glass

### 2 Standoff Pairs With 4" Spacing

<b>Glass Width (in)</b>	36	48	60	72
<b>Allowable Height (in)</b>	N/A	N/A	N/A	N/A

### 3 Standoff Pairs With 4" Spacing

<b>Glass Width (in)</b>	36	48	60	72
<b>Allowable Height (in)</b>	36	42	36	36

### 2 Standoff Pairs With 6" Spacing

<b>Glass Width (in)</b>	36	48	60	72
<b>Allowable Height (in)</b>	36	36	36	N/A

### 3 Standoff Pairs With 6" Spacing

<b>Glass Width (in)</b>	36	48	60	72
<b>Allowable Height (in)</b>	42	42	42	42

NOTE: Heights are measured beginning at upper standoff